

# Tordeck™ PB

## System data sheet



Providing Practical Solutions



### System features

- 2 coat liquid applied waterproof membrane
- Slip resistant finish
- Cold applied system
- Excellent durability
- Seamless system
- Colour choice available\*

\*Dark grey is our standard colour. Other colours can be made to order.

### What does the system include?

- 1st Coat** Optional - use on porous substrates  
**Torcure™ MC Binder/Sealer** (PU885) is a single pack penetrating sealer for the stabilisation and consolidation of porous or friable substrates.
- 2nd Coat** **Elastaseal™ Fibretex** is a single pack fibre reinforced coating used as a basecoat in the system.
- 3rd Coat** **Tordeck™ PB Topcoat** is a single pack coating with aluminium oxide anti-slip grits added to the wet resin. This is used as the finishing and weathering coat of the **Tordeck™ PB** system.

### Product Appearance

Textured slip resistant coloured floor finish.

### What does it do?

**Tordeck™ PB** system is a hard wearing resin flooring system designed to waterproof private balconies and provide a slip resistant finish.

### Where can it be used?

#### Substrates

The system is specifically intended for use on asphalt and concrete.

#### Buildings

**Tordeck™ PB** system is suitable for small balconies usually found in:

- Social Housing Blocks
- Private residential housing
- Residential care homes

### The Tor service available to you

- Unrivalled expertise and knowledge
- Nationwide team of area managers / technical personnel
- Free site survey
- Free specification service (NBS format also available)
- On-site technical back-up on live projects



## Technical information

	Torcure™ MC Binder/Sealer	Elastaseal™ Fibretex	Tordeck™ PB Topcoat
<b>Theoretical coverage</b>	Up to 16m <sup>2</sup> per litre	1.25m <sup>2</sup> per litre	2m <sup>2</sup> per litre
<b>Application</b>	Brush / roller	Brush / short-medium pile fleecy roller / Squeegee	Brush / short-medium pile fleecy roller
<b>Pack size</b>	5 Litres	5 Litres	5 Litres
<b>Touch dry</b>	2 hours	4 hours	4 hours
<b>Hard dry</b>	4 hours	16 hours	12 hours
<b>Minimum overcoating time</b>	4 hours	16 hours	12 hours
<b>Maximum overcoating interval</b>	24 hours	7 days	3 days

**Note:** Coverage rate may vary depending on substrate condition, environment etc (in the case of Torcure™ MC Binder/Sealer, a typical coverage rate on concrete will be in the region of 12m<sup>2</sup> per litre on asphalt). A copy of the appropriate Technical Data Sheets and Health and Safety Data Sheets should be consulted prior to using the products.

## How to specify

The following specifications are included for demonstrative purposes only. **Always consult a representative of Tor Coatings prior to specifying or applying.**

All areas should be suitably prepared according to the detailed Tor specification, prior to all application.

**Torcure™ MC Binder / Sealer** (where required)  
Ensure surfaces are below 50°C before coating. Apply 1 coat of **Torcure™ MC Binder / Sealer** (PU885) and allow to cure before applying next coat.

**Tordeck™ PB Topcoat**  
Apply 1 coat of **Elastaseal™ Fibretex** (RC104) and allow to cure overnight before overcoating.

Apply 1 coat of **Tordeck™ PB Topcoat** (RC512). Cast white aluminium oxide grits (50 mesh) onto the wet coating at 800g/m<sup>2</sup> to provide slip resistant surface-wear protection. Allow to cure.

Tor Coatings offer a free site survey service, and all of our Area Business Managers are fully trained and able to carry out full site assessments. A detailed and bespoke specification will then be issued.

Contact Tor Coatings on **0191 410 6611** to arrange your free site survey.

## Technical support



Tor Coatings' national team of Area Business Managers is supported by a dedicated customer service team, a large team of paint chemists and a dedicated technical help desk.

Call **0191 411 3148** for assistance from our helpdesk, or visit **www.tor-coatings.com** to find out more.



**www.tor-coatings.com**



Providing Practical Solutions

Tor Coatings Limited, Portobello Industrial Estate,  
Birtley, County Durham, DH3 2RE.

**Tel:** +44 (0)191 410 6611 **Fax:** +44 (0)191 492 0125

**E-mail:** enquiries@tor-coatings.com

**Web:** www.tor-coatings.com