



16-0266 Ankocryl Interior Clear Lacquer - Satin

- Version 190408 : high quality, waterborne clear satin gloss varnish.
- Composition indication : binder : specific urethane acrylic technology
- Typical characteristics : - good blocking resistance
- clear
- fast drying
- very well scratch and abrasion resistant
- less environment polluting
- good flow
- non yellowing
- Recommended uses : interior, as an abrasion resistant finish of wood. For stairs, furniture, boarding etc.
- Colour : clear

Technical Specifications (20°C and 65% R.H.)

- Solids content : approx. 35% (volume)
- Density : approx. 1,01 gr/cm³
- Viscosity : approx. 120 sec. DC4
- Gloss : available in satin, matt and naturel matt
- Drying time : - dustfree : approx. 1 hour
- recoatable : approx. 3-4 hours
- * N.B. drying speed/performance is very much dependent of temperature, humidity and particulary air speed circulation!
- Application : brush, roller, spray
- Thinner : ready to use, do not dilute
- Cleaning tools : warm water and soap



Application temperature	: min. 18°C ambient and surface temperature and relative humidity max. 85%.
Theoretical spreading rate	: at 30 micron dry: approx. 10 m ² /l.
Storage	: cool and frost-proof.
Shelf life	: minimal 12 months in unopened tin.
Special note	: for more information, see the safety data sheet of this product.

Disclaimer

The information given in this technical data sheet is only a general product description, based on our experiences and tests and therefore does not represent a specific practical case. Consequently Anker Stuy Verven doesn't guarantee the functionality or result and takes no responsibility in this respect. We advise our clients to test the applicability of the product to the nature and the state of the surfaces and to carry out the necessary representative tests in case of doubt. Please contact our R&D department as the occasion arises. Attention: our clients should verify whether the present technical data sheet hasn't been replaced by a more recent version.

