



## SAFETY DATA SHEET

### SPEEDSPRAY QDH PRIMER LIGHT GREY

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** SPEEDSPRAY QDH PRIMER LIGHT GREY

**Product number** IP010\_QDH

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** PC 9a: Coatings and paints, thinners, paint removers.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** Axalta Coating Systems Huthwaite UK Ltd  
Blackwell Road  
Huthwaite  
Nottinghamshire  
United Kingdom  
NG17 2RL  
Tel: +44 (0)1623 510585

**Contact person** info-huthwaite@axaltacs.com

##### 1.4. Emergency telephone number

**Emergency telephone** United Kingdom: 01623 528938 (Mon-Thu 0700 - 1600 hrs, Fri 0700 - 1245 hrs).

**National emergency telephone number** Republic of Ireland: National Poison Information Centre (Ireland) Tel: 01 809 2566 (8am to 10pm)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Flam. Liq. 3 - H226

**Health hazards** Acute Tox. 4 - H332 Skin Irrit. 2 - H315

**Environmental hazards** Aquatic Chronic 3 - H412

##### 2.2. Label elements

###### Hazard pictograms



**Signal word** Warning

**Hazard statements** EUH208 Contains METHYL ETHYL KETOXIME, COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.  
H226 Flammable liquid and vapour.  
H332 Harmful if inhaled.  
H315 Causes skin irritation.  
H412 Harmful to aquatic life with long lasting effects.

## SPEEDSPRAY QDH PRIMER LIGHT GREY

<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P233 Keep container tightly closed.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Contains** XYLENE

### Other information

#### 2.3. Other hazards

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>XYLENE</b> <span style="float: right;"><b>10-30%</b></span>		
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-0000
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 3 - H226	R10 Xn;R20/21 Xi;R38	
Acute Tox. 4 - H312		
Acute Tox. 4 - H332		
Skin Irrit. 2 - H315		
Asp. Tox. 1 - H304		
<b>ETHYLBENZENE</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 01-2119489370-35-0000
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 2 - H225	F;R11 Xn;R20	
Acute Tox. 4 - H332		
STOT RE 2 - H373		
Asp. Tox. 1 - H304		

## SPEEDSPRAY QDH PRIMER LIGHT GREY

<b>TRIZINC BIS(ORTHOPHOSPHATE)</b>			<b>&lt;1%</b>
CAS number: 7779-90-0	EC number: 231-944-3	REACH registration number: 01-2119485044-40-XXXX	
M factor (Acute) = 1	M factor (Chronic) = 1		
<b>Classification</b>		<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Aquatic Acute 1 - H400		N;R50/53	
Aquatic Chronic 1 - H410			
<b>METHYL ETHYL KETOXIME</b>			<b>&lt;1%</b>
CAS number: 96-29-7	EC number: 202-496-6	REACH registration number: 01-2119539477-28-0000	
<b>Classification</b>		<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Acute Tox. 4 - H312		Carc. Cat. 3;R40 Xn;R21 R43 Xi;R41	
Eye Dam. 1 - H318			
Skin Sens. 1 - H317			
Carc. 2 - H351			
<b>COBALT BIS(2-ETHYLHEXANOATE)</b>			<b>&lt;1%</b>
CAS number: 136-52-7	EC number: 205-250-6	REACH registration number: 01-2119524678-29-0000	
M factor (Acute) = 1			
<b>Classification</b>			
Eye Irrit. 2 - H319			
Skin Sens. 1A - H317			
Repr. 1B - H360F			
Aquatic Acute 1 - H400			
Aquatic Chronic 3 - H412			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**Composition comments**      The data shown are in accordance with the latest EC Directives.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if symptoms are severe or persist.
<b>Ingestion</b>	Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Give a few small glasses of water or milk to drink. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention.
<b>Skin contact</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.

## SPEEDSPRAY QDH PRIMER LIGHT GREY

**Eye contact** Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 15 minutes. Get medical attention if symptoms are severe or persist after washing.

### 4.2. Most important symptoms and effects, both acute and delayed

**General information** No data available on the mixture itself.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with the following media: Foam. Dry chemicals, sand, dolomite etc.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** The product is flammable. Heating may generate flammable vapours.

**Hazardous combustion products** Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO).

### 5.3. Advice for firefighters

**Protective actions during firefighting** Move containers from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet.

**For non-emergency personnel** Keep unnecessary and unprotected personnel away from the area.

### 6.2. Environmental precautions

**Environmental precautions** Use appropriate containment to avoid environmental contamination.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry, cool and well-ventilated place.

**Storage class** Flammable liquid storage.

### 7.3. Specific end use(s)

## SPEEDSPRAY QDH PRIMER LIGHT GREY

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m<sup>3</sup>(Sk)

Occupational Exposure Limits (Ireland):

Long-term exposure limit (8-hour TWA): NAOSH (Ireland) OELV 8 hours; 50 ppm 221 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): NAOSH (Ireland) OELV-15 min 100 ppm 442 mg/m<sup>3</sup>

##### ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m<sup>3</sup>

Sk

Occupational Exposure Limits (Ireland):

Long-term exposure limit (8-hour TWA): NAOSH (Ireland) OELV 8 hours; 100 ppm 442 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): NAOSH (Ireland) OELV-15 min 200 ppm 884 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

**Ingredient comments** WEL = Workplace Exposure Limits

#### METHYL ETHYL KETOXIME (CAS: 96-29-7)

##### DNEL

Workers - Dermal; Short term systemic effects: 2.5 mg/kg/day

Workers - Dermal; Long term systemic effects: 1.3 mg/kg/day

Workers - Inhalation; Long term systemic effects: 9 mg/m<sup>3</sup>

Workers - Inhalation; Long term local effects: 3.33 mg/m<sup>3</sup>

Consumer - Dermal; Short term systemic effects: 1.5 mg/kg/day

Consumer - Dermal; Long term systemic effects: 0.78 mg/kg/day

Consumer - Inhalation; Long term systemic effects: 2.7 mg/m<sup>3</sup>

Consumer - Inhalation; Long term local effects: 2 mg/m<sup>3</sup>

#### 8.2. Exposure controls

##### Protective equipment



##### Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

##### Eye/face protection

If a risk assessment indicates eye contact is possible, suitable eye protection should be worn e.g. safety spectacles, safety goggles or a faceshield as appropriate. Personal protective equipment for eye and face protection should comply with European Standard EN166.

## SPEEDSPRAY QDH PRIMER LIGHT GREY

<b>Hand protection</b>	Wear protective gloves. To protect hands from chemicals, gloves should comply with European Standard EN374. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber; thickness 0.35mm minimum. Butyl Rubber; thickness 0.5mm minimum. Fluorinated rubber (Viton); thickness 0.4mm minimum. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. The breakthrough time for any glove material may be different for different glove manufacturers. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.
<b>Other skin and body protection</b>	Wear appropriate clothing to prevent any possibility of skin contact.
<b>Hygiene measures</b>	Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
<b>Respiratory protection</b>	If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P2. Check that the respirator fits tightly and the filter is changed regularly.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Viscous liquid.
<b>Colour</b>	Grey.
<b>Odour</b>	Characteristic.
<b>Initial boiling point and range</b>	137°C
<b>Flash point</b>	25°C Closed cup.
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 1.1% Upper flammable/explosive limit: 7%
<b>Vapour pressure</b>	Not available.
<b>Relative density</b>	1.41 - 1.45
<b>Solubility(ies)</b>	Immiscible with water.
<b>Partition coefficient</b>	Not available.

#### 9.2. Other information

<b>Other information</b>	No additional information
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 480 g/l.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	See the other subsections of this section for further details.
-------------------	----------------------------------------------------------------

#### 10.2. Chemical stability

<b>Stability</b>	Stable at normal ambient temperatures.
------------------	----------------------------------------

#### 10.3. Possibility of hazardous reactions

## SPEEDSPRAY QDH PRIMER LIGHT GREY

**Possibility of hazardous reactions** Under normal conditions of storage and use, no hazardous reactions will occur.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition.

### 10.5. Incompatible materials

**Materials to avoid** Avoid contact with the following materials: Acids. Oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - dermal

**ATE dermal (mg/kg)** 4,688.86

#### Acute toxicity - inhalation

**ATE inhalation (gases ppm)** 17,263.54

**ATE inhalation (vapours mg/l)** 42.2

**ATE inhalation (dusts/mists mg/l)** 5.75

**General information** Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

**Inhalation** Harmful by inhalation. Gas or vapour in high concentrations may irritate the respiratory system. Solvent vapours are hazardous and may cause nausea, sickness and headaches. Symptoms following overexposure may include the following: Coughing.

**Ingestion** Gastrointestinal symptoms, including upset stomach.

**Skin contact** Irritating to skin. May cause an allergic skin reaction. Prolonged and frequent contact may cause redness and irritation.

**Eye contact** Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

## SECTION 12: Ecological information

**Ecotoxicity** The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

### 12.1. Toxicity

**Toxicity** No data on the mixture itself.

### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

## SPEEDSPRAY QDH PRIMER LIGHT GREY

### 12.4. Mobility in soil

**Mobility** No data available.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

**Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Waste should be treated as controlled waste.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

## SECTION 14: Transport information

### 14.1. UN number

**UN No. (ADR/RID)** 1263

**UN No. (IMDG)** 1263

**UN No. (ICAO)** 1263

**UN No. (ADN)** 1263

### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** PAINT

**Proper shipping name (IMDG)** PAINT

**Proper shipping name (ICAO)** PAINT

**Proper shipping name (ADN)** PAINT

### 14.3. Transport hazard class(es)

**ADR/RID class** 3

**ADR/RID classification code** F1

**ADR/RID label** 3

**IMDG class** 3

**ICAO class/division** 3

**ADN class** 3

### Transport labels



### 14.4. Packing group

**ADR/RID packing group** III

**IMDG packing group** III



## SPEEDSPRAY QDH PRIMER LIGHT GREY

ICAO packing group III

ADN packing group III

### 14.5. Environmental hazards

**Environmentally hazardous substance/marine pollutant**

No.

### 14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 3

Emergency Action Code •3Y

Hazard Identification Number (ADR/RID) 30

Tunnel restriction code (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UFI UFI: TKSU-U24E-W00S-5WP4

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

**Guidance** Workplace Exposure Limits EH40.  
2018 Code of Practice for the Chemical Agents Regulations (HSA Ireland)

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

**Abbreviations and acronyms used in the safety data sheet** WEL: Workplace Exposure Limit.  
ATE: Acute Toxicity Estimate.  
CAS: Chemical Abstracts Service.  
DMEL: Derived Minimal Effect Level.  
DNEL: Derived No Effect Level.  
OELV: Occupational Exposure Limit Value.  
PNEC: Predicted No Effect Concentration.  
PBT: Persistent, Bioaccumulative and Toxic substance.  
vPvB: Very Persistent and Very Bioaccumulative.

Revision date 20/08/2019

Revision 4

Supersedes date 11/12/2018

## SPEEDSPRAY QDH PRIMER LIGHT GREY

<b>SDS number</b>	32422
<b>Risk phrases in full</b>	R10 Flammable. R11 Highly flammable. R20 Harmful by inhalation. R20/21 Harmful by inhalation and in contact with skin. R21 Harmful in contact with skin. R38 Irritating to skin. R40 Limited evidence of a carcinogenic effect. R41 Risk of serious damage to eyes. R43 May cause sensitisation by skin contact. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking.
<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H351 Suspected of causing cancer. H360F May damage fertility. H373 May cause damage to organs (Hearing organs) through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH208 Contains METHYL ETHYL KETOXIME, COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.

The information in this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.