



## SAFETY DATA SHEET SPEEDSPRAY QDH PRIMER BLACK

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** SPEEDSPRAY QDH PRIMER BLACK

**Product number** IP014\_QDH

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** PC 9a: Coatings and paints, thinners, paint removers.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** Axalta Coating Systems Huthwaite UK Ltd  
Blackwell Road  
Huthwaite  
Nottinghamshire  
NG17 2RL  
Tel: +44 (0)1623 510585

**Contact person** info-huthwaite@axaltacs.com

#### 1.4. Emergency telephone number

**Emergency telephone** +44 (0)1623 528938 (Not 24 Hours)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

**Physical hazards** Flam. Liq. 3 - H226

**Health hazards** Acute Tox. 4 - H332 Skin Irrit. 2 - H315 STOT RE 2 - H373

**Environmental hazards** Aquatic Chronic 3 - H412

#### 2.2. Label elements

##### Pictogram



**Signal word** Warning

**Hazard statements** H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H332 Harmful if inhaled.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.  
EUH208 Contains METHYL ETHYL KETOXIME, COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.

## SPEEDSPRAY QDH PRIMER BLACK

<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P233 Keep container tightly closed.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	---

**Contains** XYLENE, NAPHTHA (PETROLEUM), HYDRODESULPHURISED HEAVY, ETHYLBENZENE

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

<b>XYLENE</b>		<b>10-30%</b>
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-0000
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 3 - H226	R10 Xn;R20/21 Xi;R38	
Acute Tox. 4 - H312		
Acute Tox. 4 - H332		
Skin Irrit. 2 - H315		
Asp. Tox. 1 - H304		
<b>NAPHTHA (PETROLEUM), HYDRODESULPHURISED HEAVY</b>		<b>1-5%</b>
CAS number: 64742-82-1	EC number: 919-446-0	REACH registration number: 01-2119458049-33-0000
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 3 - H226	T; R48/23/24/25. Xn; R65. N; R51/53. R10, R67	
STOT SE 3 - H336		
STOT RE 1 - H372		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		

**SPEEDSPRAY QDH PRIMER BLACK**

<b>ETHYLBENZENE</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 01-2119489370-35-0000
<b>Classification</b> Flam. Liq. 2 - H225 Acute Tox. 4 - H332 Asp. Tox. 1 - H304	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 Xn;R20	
<b>TRIZINC BIS(ORTHOPHOSPHATE)</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 7779-90-0	EC number: 231-944-3	REACH registration number: 01-2119485044-40-XXXX
M factor (Acute) = 1	M factor (Chronic) = 1	
<b>Classification</b> Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	<b>Classification (67/548/EEC or 1999/45/EC)</b> N;R50/53	
<b>METHYL ETHYL KETOXIME</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 96-29-7	EC number: 202-496-6	REACH registration number: 01-2119539477-28-0000
<b>Classification</b> Acute Tox. 4 - H312 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Carc. 2 - H351	<b>Classification (67/548/EEC or 1999/45/EC)</b> Carc. Cat. 3;R40 Xn;R21 R43 Xi;R41	
<b>NAPHTHA (PETROLEUM), HYDROTREATED HEAVY</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 64742-48-9	EC number: 265-150-3	REACH registration number: 01-2119486659-16-0000
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R65. R10,R66.	
<b>PROPIONIC ACID</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 79-09-4	EC number: 201-176-3	REACH registration number: 01-2119486971-24-XXXX
<b>Classification</b> Flam. Liq. 3 - H226 Skin Corr. 1B - H314 Eye Dam. 1 - H318 STOT SE 3 - H335	<b>Classification (67/548/EEC or 1999/45/EC)</b> C;R34	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SPEEDSPRAY QDH PRIMER BLACK

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. If in doubt, get medical attention promptly.
<b>Ingestion</b>	Give a few small glasses of water or milk to drink. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person.
<b>Skin contact</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 10 minutes. Get medical attention if irritation persists after washing.

#### 4.2. Most important symptoms and effects, both acute and delayed

**General information** No data available on the mixture itself.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with the following media: Alcohol-resistant foam. Carbon dioxide (CO <sub>2</sub> ). Dry chemicals, sand, dolomite etc.
<b>Unsuitable extinguishing media</b>	Do not use water, if avoidable.

#### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	The product is flammable. Heating may generate flammable vapours.
<b>Hazardous combustion products</b>	Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Carbon dioxide (CO <sub>2</sub> ). Carbon monoxide (CO).

#### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	Move containers from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Wear protective clothing as described in Section 8 of this safety data sheet.
<b>For non-emergency personnel</b>	Keep unnecessary and unprotected personnel away from the area.

#### 6.2. Environmental precautions

<b>Environmental precautions</b>	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

#### 6.3. Methods and material for containment and cleaning up

## SPEEDSPRAY QDH PRIMER BLACK

**Methods for cleaning up** Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry, cool and well-ventilated place.

**Storage class** Flammable liquid storage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m<sup>3</sup>(Sk)

##### NAPHTHA (PETROLEUM), HYDRODESULPHURISED HEAVY

Long-term exposure limit (8-hour TWA): OES 600 mg/m<sup>3</sup>

##### ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 441 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 125 ppm(Sk) 552 mg/m<sup>3</sup>(Sk)

##### NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m<sup>3</sup>

##### PROPIONIC ACID

Long-term exposure limit (8-hour TWA): WEL 10 ppm 31 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 15 ppm 46 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

### 8.2. Exposure controls

#### Protective equipment



**Appropriate engineering controls**

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

**Eye/face protection**

If a risk assessment indicates eye contact is possible, suitable eye protection should be worn e.g. safety spectacles, safety goggles or a faceshield as appropriate. Personal protective equipment for eye and face protection should comply with European Standard EN166.

## SPEEDSPRAY QDH PRIMER BLACK

<b>Hand protection</b>	Wear protective gloves. To protect hands from chemicals, gloves should comply with European Standard EN374. For exposure up to 8 hours, wear gloves made of the following material: Nitrile rubber; thickness 0.35mm minimum. Butyl Rubber; thickness 0.5mm minimum. Fluorinated rubber (Viton); thickness 0.4mm minimum. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. The breakthrough time for any glove material may be different for different glove manufacturers. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.
<b>Other skin and body protection</b>	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station. Use engineering controls to reduce air contamination to permissible exposure level.
<b>Hygiene measures</b>	Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
<b>Respiratory protection</b>	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Viscous liquid.
<b>Colour</b>	Black.
<b>Odour</b>	Characteristic.
<b>Initial boiling point and range</b>	137°C
<b>Flash point</b>	25°C Closed cup.
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 1.1% Upper flammable/explosive limit: 7%
<b>Vapour pressure</b>	Not available.
<b>Relative density</b>	1.36 - 1.40
<b>Solubility(ies)</b>	Immiscible with water.
<b>Partition coefficient</b>	Not available.

#### 9.2. Other information

<b>Other information</b>	No additional information
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 483 g/l.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	See the other subsections of this section for further details.
-------------------	--

#### 10.2. Chemical stability

<b>Stability</b>	Stable at normal ambient temperatures.
------------------	--

#### 10.3. Possibility of hazardous reactions

## SPEEDSPRAY QDH PRIMER BLACK

**Possibility of hazardous reactions** Under normal conditions of storage and use, no hazardous reactions will occur.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition.

### 10.5. Incompatible materials

**Materials to avoid** Avoid contact with the following materials: Acids. Oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - dermal

**ATE dermal (mg/kg)** 3,880.87

#### Acute toxicity - inhalation

**ATE inhalation (gases ppm)** 14,288.66

**ATE inhalation (vapours mg/l)** 34.93

**ATE inhalation (dusts/mists mg/l)** 4.76

**Inhalation** Harmful by inhalation. May cause respiratory system irritation.

**Ingestion** Harmful if swallowed.

**Skin contact** Harmful in contact with skin. Irritating to skin.

**Eye contact** May irritate eyes.

**Target organs** Skin Eyes Respiratory system, lungs

## SECTION 12: Ecological Information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

### 12.1. Toxicity

**Toxicity** No data on the mixture itself.

### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

### 12.4. Mobility in soil

**Mobility** No data available.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

## SPEEDSPRAY QDH PRIMER BLACK

### 12.6. Other adverse effects

Other adverse effects                      None known.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal methods**                      Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### SECTION 14: Transport information

#### 14.1. UN number

UN No. (ADR/RID)                      1263

UN No. (IMDG)                          1263

UN No. (ICAO)                          1263

UN No. (ADN)                            1263

#### 14.2. UN proper shipping name

Proper shipping name                  PAINT  
(ADR/RID)

Proper shipping name (IMDG)        PAINT

Proper shipping name (ICAO)        PAINT

Proper shipping name (ADN)        PAINT

#### 14.3. Transport hazard class(es)

ADR/RID class                            3

ADR/RID classification code        F1

ADR/RID label                            3

IMDG class                                3

ICAO class/division                  3

ADN class                                 3

#### Transport labels



#### 14.4. Packing group

ADR/RID packing group                III

IMDG packing group                    III

ADN packing group                    III

ICAO packing group                    III

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant  
No.

#### 14.6. Special precautions for user



## SPEEDSPRAY QDH PRIMER BLACK

<b>EmS</b>	F-E, S-E
<b>ADR transport category</b>	3
<b>Emergency Action Code</b>	•3Y
<b>Hazard Identification Number (ADR/RID)</b>	30
<b>Tunnel restriction code</b>	(D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

**Guidance** Workplace Exposure Limits EH40.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### **SECTION 16: Other information**

**Abbreviations and acronyms used in the safety data sheet** WEL: Workplace Exposure Limit.  
ATE: Acute Toxicity Estimate.  
CAS: Chemical Abstracts Service.  
DMEL: Derived Minimal Effect Level.  
DNEL: Derived No Effect Level.  
PNEC: Predicted No Effect Concentration.  
PBT: Persistent, Bioaccumulative and Toxic substance.  
vPvB: Very Persistent and Very Bioaccumulative.

<b>Revision date</b>	18/06/2018
<b>Revision</b>	3
<b>Supersedes date</b>	30/10/2017
<b>SDS number</b>	32429

## SPEEDSPRAY QDH PRIMER BLACK

### Risk phrases in full

R10 Flammable.  
R11 Highly flammable.  
R20 Harmful by inhalation.  
R20/21 Harmful by inhalation and in contact with skin.  
R21 Harmful in contact with skin.  
R38 Irritating to skin.  
R40 Limited evidence of a carcinogenic effect.  
R41 Risk of serious damage to eyes.  
R43 May cause sensitisation by skin contact.  
R48/20/21/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.  
R48/23/24/25 Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.  
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.

### Hazard statements in full

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.  
EUH208 Contains METHYL ETHYL KETOXIME, COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.