



## SAFETY DATA SHEET

### SPEEDSPRAY QDH PRIMER WHITE

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name SPEEDSPRAY QDH PRIMER WHITE

Product number IP015\_QDH

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses PC 9a: Coatings and paints, thinners, paint removers.

##### 1.3. Details of the supplier of the safety data sheet

Supplier Axalta Coating Systems Huthwaite UK Ltd  
Blackwell Road  
Huthwaite  
Nottinghamshire  
NG17 2RL  
Tel: +44 (0)1623 510585

Contact person info-huthwaite@axaltacs.com

##### 1.4. Emergency telephone number

Emergency telephone +44 (0)1623 528938 (Not 24 Hours)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)


Physical hazards Flam. Liq. 3 - H226

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315

Environmental hazards Aquatic Chronic 3 - H412

##### 2.2. Label elements

###### Pictogram



Signal word Warning

Hazard statements H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H332 Harmful if inhaled.  
H412 Harmful to aquatic life with long lasting effects.  
EUH208 Contains METHYL ETHYL KETOXIME, COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.

## SPEEDSPRAY QDH PRIMER WHITE

<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P233 Keep container tightly closed.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	---

**Contains** XYLENE, ETHYLBENZENE

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>XYLENE</b>	<b>10-30%</b>
CAS number: 1330-20-7	EC number: 215-535-7
	REACH registration number: 01-2119488216-32-0000
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 3 - H226	R10 Xn;R20/21 Xi;R38
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Asp. Tox. 1 - H304	
<b>ETHYLBENZENE</b>	<b>1-5%</b>
CAS number: 100-41-4	EC number: 202-849-4
	REACH registration number: 01-2119489370-35-0000
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 2 - H225	F;R11 Xn;R20
Acute Tox. 4 - H332	
Asp. Tox. 1 - H304	
<b>TRIZINC BIS(ORTHOPHOSPHATE)</b>	<b>&lt;1%</b>
CAS number: 7779-90-0	EC number: 231-944-3
	REACH registration number: 01-2119485044-40-XXXX
M factor (Acute) = 1	M factor (Chronic) = 1
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Aquatic Acute 1 - H400	N;R50/53
Aquatic Chronic 1 - H410	

## SPEEDSPRAY QDH PRIMER WHITE

<b>METHYL ETHYL KETOXIME</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 96-29-7	EC number: 202-496-6	REACH registration number: 01-2119539477-28-0000
<b>Classification</b>		<b>Classification (67/548/EEC or 1999/45/EC)</b>
Acute Tox. 4 - H312		Carc. Cat. 3;R40 Xn;R21 R43 Xi;R41
Eye Dam. 1 - H318		
Skin Sens. 1 - H317		
Carc. 2 - H351		
<b>NAPHTHA (PETROLEUM), HYDROTREATED HEAVY</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 64742-48-9	EC number: 265-150-3	REACH registration number: 01-2119486659-16-0000
<b>Classification</b>		<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 3 - H226		Xn;R65. R10,R66.
STOT SE 3 - H336		
Asp. Tox. 1 - H304		
<b>PROPIONIC ACID</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 79-09-4	EC number: 201-176-3	REACH registration number: 01-2119486971-24-XXXX
<b>Classification</b>		<b>Classification (67/548/EEC or 1999/45/EC)</b>
Flam. Liq. 3 - H226		C;R34
Skin Corr. 1B - H314		
Eye Dam. 1 - H318		
STOT SE 3 - H335		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**Composition comments**      The data shown are in accordance with the latest EC Directives.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
<b>Skin contact</b>	Immediately remove contaminated clothing. Rinse immediately with plenty of water.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

## SPEEDSPRAY QDH PRIMER WHITE

### 4.2. Most important symptoms and effects, both acute and delayed

**General information**                      Treat symptomatically.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor**                      Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media**      Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards**                          The product is flammable. Heating may generate flammable vapours.

**Hazardous combustion products**      Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Oxides of carbon.

### 5.3. Advice for firefighters

**Protective actions during firefighting**      Move containers from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out.

**Special protective equipment for firefighters**      Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions**                      Wear protective clothing as described in Section 8 of this safety data sheet.

**For non-emergency personnel**      Keep unnecessary and unprotected personnel away from the area.

### 6.2. Environmental precautions

**Environmental precautions**      Do not discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up**                      Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

### 6.4. Reference to other sections

**Reference to other sections**      For personal protection, see Section 8. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions**                          Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions**                          Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents.

**Storage class**                                  Flammable liquid storage.

### 7.3. Specific end use(s)

## SPEEDSPRAY QDH PRIMER WHITE

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### **XYLENE**

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m<sup>3</sup>(Sk)

##### **ETHYLBENZENE**

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 441 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 125 ppm(Sk) 552 mg/m<sup>3</sup>(Sk)

##### **NAPHTHA (PETROLEUM), HYDROTREATED HEAVY**

Long-term exposure limit (8-hour TWA): WEL 1000 mg/m<sup>3</sup>

##### **PROPIONIC ACID**

Long-term exposure limit (8-hour TWA): WEL 10 ppm 31 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 15 ppm 46 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

#### **Ingredient comments**

WEL = Workplace Exposure Limits

#### 8.2. Exposure controls

##### **Protective equipment**



##### **Appropriate engineering controls**

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

##### **Eye/face protection**

If a risk assessment indicates eye contact is possible, suitable eye protection should be worn e.g. safety spectacles, safety goggles or a faceshield as appropriate. Personal protective equipment for eye and face protection should comply with European Standard EN166.

##### **Hand protection**

Wear protective gloves. To protect hands from chemicals, gloves should comply with European Standard EN374. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber; thickness 0.35mm minimum. Butyl Rubber; thickness 0.5mm minimum. Fluorinated rubber (Viton); thickness 0.4mm minimum. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. The breakthrough time for any glove material may be different for different glove manufacturers. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

##### **Other skin and body protection**

Wear appropriate clothing to prevent any possibility of skin contact.

##### **Hygiene measures**

Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

## SPEEDSPRAY QDH PRIMER WHITE

**Respiratory protection**      Wear a respirator fitted with the following cartridge: Organic vapour filter.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Viscous liquid.
<b>Colour</b>	White.
<b>Odour</b>	Characteristic.
<b>Initial boiling point and range</b>	137°C
<b>Flash point</b>	25°C Closed cup.
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 1.1% Upper flammable/explosive limit: 7%
<b>Vapour pressure</b>	Not available.
<b>Relative density</b>	1.42 - 1.46
<b>Solubility(ies)</b>	Immiscible with water.
<b>Partition coefficient</b>	Not available.

#### 9.2. Other information

<b>Other information</b>	No additional information
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 474 grams per Litre .

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	See the other subsections of this section for further details.
-------------------	--

#### 10.2. Chemical stability

<b>Stability</b>	Stable at normal ambient temperatures.
------------------	--

#### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	Under normal conditions of storage and use, no hazardous reactions will occur.
---	--

#### 10.4. Conditions to avoid

<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition.
----------------------------	---

#### 10.5. Incompatible materials

<b>Materials to avoid</b>	Avoid contact with the following materials: Acids. Oxidising agents.
---------------------------	--

#### 10.6. Hazardous decomposition products

<b>Hazardous decomposition products</b>	Oxides of carbon.
---	-------------------

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity - dermal

<b>ATE dermal (mg/kg)</b>	3,667.14
---------------------------	----------

##### Acute toxicity - inhalation

## SPEEDSPRAY QDH PRIMER WHITE

ATE inhalation (gases ppm) 13,501.76

ATE inhalation (vapours mg/l) 33.0

ATE inhalation (dusts/mists mg/l) 4.5

<b>General information</b>	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
<b>Inhalation</b>	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Harmful by inhalation.
<b>Ingestion</b>	Gastrointestinal symptoms, including upset stomach.
<b>Skin contact</b>	Product has a defatting effect on skin. May cause allergic contact eczema. Irritating to skin.
<b>Eye contact</b>	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

### SECTION 12: Ecological Information

**Ecotoxicity** The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

#### 12.1. Toxicity

**Toxicity** No data on the mixture itself.

#### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

#### 12.4. Mobility in soil

**Mobility** No data available.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

**Other adverse effects** None known.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**General information** Waste should be treated as controlled waste.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### SECTION 14: Transport information

#### 14.1. UN number

**UN No. (ADR/RID)** 1263

## SPEEDSPRAY QDH PRIMER WHITE

UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT
Proper shipping name (IMDG)	PAINT
Proper shipping name (ICAO)	PAINT
Proper shipping name (ADN)	PAINT

### 14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

#### Transport labels



### 14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant  
No.

### 14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code



## SPEEDSPRAY QDH PRIMER WHITE

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

**Guidance** Workplace Exposure Limits EH40.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

**Abbreviations and acronyms used in the safety data sheet** WEL: Workplace Exposure Limit.  
ATE: Acute Toxicity Estimate.  
CAS: Chemical Abstracts Service.  
DMEL: Derived Minimal Effect Level.  
DNEL: Derived No Effect Level.  
PNEC: Predicted No Effect Concentration.  
PBT: Persistent, Bioaccumulative and Toxic substance.  
vPvB: Very Persistent and Very Bioaccumulative.

**Revision date** 19/06/2018

**Revision** 3

**Supersedes date** 01/02/2016

**SDS number** 32431

**Risk phrases in full** R10 Flammable.  
R11 Highly flammable.  
R20 Harmful by inhalation.  
R20/21 Harmful by inhalation and in contact with skin.  
R21 Harmful in contact with skin.  
R38 Irritating to skin.  
R40 Limited evidence of a carcinogenic effect.  
R41 Risk of serious damage to eyes.  
R43 May cause sensitisation by skin contact.  
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.

## SPEEDSPRAY QDH PRIMER WHITE

### Hazard statements in full

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.  
EUH208 Contains METHYL ETHYL KETOXIME, COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.