



Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.bondaglass.com

October 2020

PRODUCT DATA SHEET

Product	APW Soft Wax Release Agent
Type	Wax-based mould release agent
Intended Use	Used to release polyurethane foams and casting compounds from moulds with complicated and porous surfaces.
Special Features	Universal soft wax-based release agent for rigid mould compounds including plaster, GRP, metal, wood and glass. May also be used on production equipment such as scales and casting tables to assist in cleaning.
Preparation	Ensure mould is clean before starting. Some porous surfaces such as plaster and timber may need sealing before release wax is applied.
Application	Apply with a cloth or sponge.
Coats	May be applied several times depending on porosity of mould and if mould is new
Drying Time	15 – 60 minutes depending on ambient conditions.
Re-coating Time	15 – 60 minutes depending on ambient conditions.
Application Temp.	Ideally 15 – 25 degrees Centigrade
Coverage	50g per square meter.
Maintenance	Not applicable.
Compatibility	May be used on plaster, GRP, metal, wood and glass. Check product suitability.
Settlement	Stir well before use.
Shelf-life/Storage	Several years if suitably stored in unopened containers. Avoid frost. Avoid heat.
Hazards	Causes serious eye irritation. Wear protective gloves/eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical attention. Avoid release into the environment. Collect spillage.
Clean-Up	Wash equipment with white spirit
Sizes	500g