

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Bonda Marine Wood Seal
Product code : BON1218-
Type of product : Paste
Product group : End product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Professional use, Industrial use
Use of the substance/mixture : Adhesives, binding agents
Function or use category : Adhesives, binding agents

1.2.2. Uses advised against

Restrictions on use : Adhesives, sealants

1.3. Details of the supplier of the safety data sheet

Manufacturer

Bondaglass Voss Ltd
Rustins Ltd
Waterloo road
NW2 7TX London
United Kingdom
T +44 (0)208 450 4666 , F +44 (0)208 452 2008
rustins@rustins.co.uk, rustins.ltd

Distributor

Excellence Ltd
43 Grange Parade,
Unit 43
Baldoyle Industrial Estate,
D13 Y860 Dublin
Ireland
T 00353 (0)1 8323300, F 00353 (0)1 8323584
Orders@excellence.ie, www.excellence.ie

1.4. Emergency telephone number

Emergency number : +44 (0)208 450 4666
OFFICE HOURS ONLY MON. - FRI. 08:00 - 16.30

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Acute toxicity (inhalation:dust,mist) Category 4 H332
Skin sensitisation, Category 1 H317
Specific target organ toxicity – Single exposure, Category 3, H336
Narcosis

Bonda Marine Wood Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific target organ toxicity – Single exposure, Category 3, H335
Respiratory tract irritation
Hazardous to the aquatic environment – Acute Hazard, H400
Category 1
Hazardous to the aquatic environment – Chronic Hazard, H411
Category 2
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Harmful if inhaled. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

EUH-statements

Extra phrases

- :
: Warning
: PROPYL BENZENE; Hydrocarbons, C9, aromatics; Aliphatic Polyisocyanate based on HDI; 1,2,4-TRIMETHYLBENZENE; mesitylene; 1,3,5-trimethylbenzene; hexamethylene-di-isocyanate
: H226 - Flammable liquid and vapour.
H317 - May cause an allergic skin reaction.
H332 - Harmful if inhaled.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.
H410 - Very toxic to aquatic life with long lasting effects.
: P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear eye protection, face protection.
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a POISON CENTER if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
: EUH204 - Contains isocyanates. May produce an allergic reaction.
: As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Bonda Marine Wood Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9, aromatics	CAS-No.: 64742-95-6 EC-No.: 918-668-5 REACH-no: 01-2119455851-35	53 – 63	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Aliphatic Polyisocyanate based on HDI	CAS-No.: 67892-85-7	30 – 40	Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 STOT SE 3, H335
1,2,4-TRIMETHYLBENZENE	CAS-No.: 95-63-6 EC-No.: 202-436-9 EC Index-No.: 601-043-00-3	1 – 10	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411
PROPYL BENZENE	CAS-No.: 103-65-1 EC-No.: 203-132-9	1 – 5	Flam. Liq. 3, H226 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
mesitylene; 1,3,5-trimethylbenzene	CAS-No.: 108-67-8 EC-No.: 203-604-4 EC Index-No.: 601-025-00-5	0.1 – 5	Flam. Liq. 3, H226 STOT SE 3, H335 Aquatic Chronic 2, H411
xylene substance with national workplace exposure limit(s) (GB, IE)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119475791-29	< 1	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
hexamethylene-di-isocyanate	CAS-No.: 822-06-0 EC-No.: 212-485-8 EC Index-No.: 615-011-00-1	< 1	Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Inhalation:dust,mist), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335

Bonda Marine Wood Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
mesitylene; 1,3,5-trimethylbenzene	CAS-No.: 108-67-8 EC-No.: 203-604-4 EC Index-No.: 601-025-00-5	(25 ≤ C ≤ 100) STOT SE 3, H335
hexamethylene-di-isocyanate	CAS-No.: 822-06-0 EC-No.: 212-485-8 EC Index-No.: 615-011-00-1	(0.5 ≤ C ≤ 100) Resp. Sens. 1, H334 (0.5 ≤ C ≤ 100) Skin Sens. 1, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Bonda Marine Wood Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Bonda Marine Wood Seal	
Ireland - Occupational Exposure Limits	
Local name	4,4'-Methylene-diphenyl diisocyanate (as —NCO) [MDI]
OEL TWA	0.005 ppm
Remark	Sens. (In the workplace respiratory or dermal exposures to sensitising agents may occur. Sensitizers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The notation does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitizers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))

Bonda Marine Wood Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Bonda Marine Wood Seal	
Regulatory reference	Chemical Agents Code of Practice 2021
xylene (1330-20-7)	
Ireland - Occupational Exposure Limits	
Local name	Xylene, mixed isomers
OEL TWA	221 mg/m ³ 50 ppm
OEL STEL	442 mg/m ³ 100 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2021
Ireland - Biological limit values	
Local name	Xylene
BMGV	1.5 g/g creatinine Parameter: methylhippuric acids - Medium: urine - Sampling time: End of Shift
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
United Kingdom - Occupational Exposure Limits	
Local name	Xylene
WEL TWA (OEL TWA)	220 mg/m ³ o-,m-,p- or mixed isomers 50 ppm o-,m-,p- or mixed isomers
WEL STEL (OEL STEL)	441 mg/m ³ o-,m-,p- or mixed isomers 100 ppm o-,m-,p- or mixed isomers
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
United Kingdom - Biological limit values	
Local name	Xylene, o-, m-, p- or mixed isomers
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

Bonda Marine Wood Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Protective clothing. Dust/aerosol mask with filter type P1.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow.
Odour	: Characteristic odour.
Odour threshold	: Not available
Melting point	: No data available.
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 43 °C
Auto-ignition temperature	: No data available.
Decomposition temperature	: Not available
pH	: 7
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available

Bonda Marine Wood Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Density	: Not available
Relative density	: No data available.
Relative vapour density at 20°C	: No data available.
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Inhalation:dust,mist: Harmful if inhaled.

Bonda Marine Wood Seal	
ATE CLP (dust,mist)	3.808 mg/l/4h
Hydrocarbons, C9, aromatics (64742-95-6)	
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 6193 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:
xylene (1330-20-7)	
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male, Remarks on results: other:
Skin corrosion/irritation	: Not classified pH: 7

Bonda Marine Wood Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C9, aromatics (64742-95-6)

pH	not applicable
Serious eye damage/irritation	: Not classified pH: 7

Hydrocarbons, C9, aromatics (64742-95-6)

pH	not applicable
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.

PROPYL BENZENE (103-65-1)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

Hydrocarbons, C9, aromatics (64742-95-6)

STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
----------------------	--

Aliphatic Polyisocyanate based on HDI (67892-85-7)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

1,2,4-TRIMETHYLBENZENE (95-63-6)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

mesitylene; 1,3,5-trimethylbenzene (108-67-8)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

xylene (1330-20-7)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

hexamethylene-di-isocyanate (822-06-0)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

Hydrocarbons, C9, aromatics (64742-95-6)

NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
----------------------------	---

xylene (1330-20-7)

LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
----------------------------	---

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Aspiration hazard	: Not classified
-------------------	------------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
-------------------	--

Bonda Marine Wood Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life.

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Hydrocarbons, C9, aromatics (64742-95-6)	
EC50 72h - Algae [1]	0.42 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.29 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

xylene (1330-20-7)	
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

12.2. Persistence and degradability

Bonda Marine Wood Seal	
Persistence and degradability	Not rapidly degradable
PROPYL BENZENE (103-65-1)	
Persistence and degradability	Not rapidly degradable
Hydrocarbons, C9, aromatics (64742-95-6)	
Persistence and degradability	Not rapidly degradable
Aliphatic Polyisocyanate based on HDI (67892-85-7)	
Persistence and degradability	Not rapidly degradable
1,2,4-TRIMETHYLBENZENE (95-63-6)	
Persistence and degradability	Not rapidly degradable
mesitylene; 1,3,5-trimethylbenzene (108-67-8)	
Persistence and degradability	Not rapidly degradable
xylene (1330-20-7)	
Persistence and degradability	Not rapidly degradable
hexamethylene-di-isocyanate (822-06-0)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

Bonda Marine Wood Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name				
PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	Paint	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
Transport document description				
UN 1263 PAINT RELATED MATERIAL, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT RELATED MATERIAL, 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	3	3
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport


Classification code (ADR) : F1
Special provisions (ADR) : 163, 367, 650
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T2
Portable tank and bulk container special provisions (ADR) : TP1, TP29

Bonda Marine Wood Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30
Orange plates :



Tunnel restriction code (ADR) : D/E
EAC code : •3Y

Transport by sea

Special provisions (IMDG) : 163, 223, 367, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provisions (IATA) : A3, A72, A192
ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1
Special provisions (ADN) : 163, 367, 650
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1
Special provisions (RID) : 163, 367, 650
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001
Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T2
Portable tank and bulk container special provisions (RID) : TP1, TP29
Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 3
Special provisions for carriage – Packages (RID) : W12
Colis express (express parcels) (RID) : CE4

Bonda Marine Wood Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard identification number (RID) : 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

VOC Directive (2004/42)

Organic solvent : Yes

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)

Bonda Marine Wood Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2

Bonda Marine Wood Seal

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH204	Contains isocyanates. May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.