

**BLACKBOARD PAINT** 

Page: 1

Compilation date: 05/07/2005

**Revision date: 26/02/2018** 

Revision No: 3

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: BLACKBOARD PAINT

Synonyms: UFI: X110-X0YF-F004-ACDH

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

Company name: FLAG Paints Ltd

8 Springfield Road

Springfield Industrial Estate

Burnham on Crouch

Essex

CM0 8UA

United Kingdom

**Tel:** +44 (0) 1621 785 173

Fax: +44 (0) 1621 785 393

Email: sales@flagpaints.co.uk

## 1.4. Emergency telephone number

Emergency tel: +44 (0) 1621 785 173

(office hours only)

#### Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; STOT RE 1: H372; Aquatic Chronic 2: H411

Most important adverse effects: Flammable liquid and vapour. Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS09: Environmental





Signal words: Danger

### **BLACKBOARD PAINT**

Page: 2

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/... equipment.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P314: Get medical advice/attention if you feel unwell.

#### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

### Hazardous ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDRODESULPHURIZED HEAVY

EINECS	CAS	PBT / WEL	CLP Classification	Percent	
265-185-4	64742-82-1	-	STOT RE 1: H372; Asp. Tox. 1: H304	30-50%	

#### Section 4: First aid measures

#### 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

### Section 5: Fire-fighting measures

**BLACKBOARD PAINT** 

Page: 3

## 5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire

brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side

up to prevent the escape of liquid.

#### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

## 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

## 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of

the area. Avoid the formation or spread of mists in the air.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

#### 7.3. Specific end use(s)

Specific end use(s): No data available.

#### Section 8: Exposure controls/personal protection

### **BLACKBOARD PAINT**

Page: 4

#### 8.1. Control parameters

### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL	
UK	300	150	-	-	

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

### Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Liquid Colour: Black

Odour: Aromatic

Solubility in water: Insoluble

Viscosity: Non-viscous

Kinematic viscosity: 6.0p

Viscosity test method: Kinematic viscosity in 10-6 m2/s at 40°C (ISO 3104/3105)

Boiling point/range°C: 200 Flash point°C: 42

Autoflammability°C: >200 Relative density: 1.2

#### 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

# 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

**BLACKBOARD PAINT** 

Page: 5

10.4. Conditions to avoid

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## **Section 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### Relevant hazards for product:

Hazard	Route	Basis
STOT-repeated exposure	-	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

## **Section 12: Ecological information**

## 12.1. Toxicity

Ecotoxicity values: No data available.

### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

#### 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

## **Section 13: Disposal considerations**

### **BLACKBOARD PAINT**

Page: 6

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## **Section 14: Transport information**

#### 14.1. UN number

UN number: UN1263

### 14.2. UN proper shipping name

Shipping name: PAINT

### 14.3. Transport hazard class(es)

Transport class: 3

# 14.4. Packing group

Packing group: III

#### 14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

## 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E
Transport category: 3

## **Section 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

# 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

#### Section 16: Other information

#### Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation

(EU) 2015/830

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

# **BLACKBOARD PAINT**

Page: 7

H372: Causes damage to organs ({{{0|||message=<or state all organs affected, if known>|||filter=(\_)?ORGAN\_.+}}}) through prolonged or repeated exposure ({{{1|||} message=<state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>|||filter=(\_)?EXP\_ROUTE\_.+}}}).

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.