

Contak Premium

Version: apr-21

Contak Premium is an adhesion bridge that provides mechanical anchoring to smooth surface plaster and adhesive mortars such as stained glass, ceramics, metals, wood, ironed concrete among others.

PRODUCT DESCRIPTION

Features:

Improves anchoring of mortars.
Excellent adhesion capacity.
Quick and easy application.
Breathable.
Outstanding resistance and durability.
Excellent flexibility. No Cracking.
Suitable for interiors and exteriors.

Technical properties:

Specific weight	1.25 ± 0.05 g/cm ³
pH	9 ± 1
Viscosity	[95-120] U.K.
Volume Solids	64 ± 5 %
Composition	Mineral particles in an acrylic emulsion
Appearance	Dense red liquid
Finish	Textured

Yield/Coverage:

Between 9-12 m²/L or 365-490 Sq.Feet per Gallon (1 coat). However, exact yield depends on type and condition of substrate, as well as tools used. Exact consumption should be determined by making onsite sample.

Pack Size:

1L, 4L, 12.5L and 15L.

Storage:

Store in original container. Keep tightly sealed in cool, dry place. Do not store in extremes of temperature, avoid direct exposure to sunlight and protect from frost. Unopened, storage stability is 36 months from

date of manufacture. Product may thicken without losing its efficacy. Shake well before use.

APPLICATION METHOD

Substrate Types:

Ideal for rendering smooth surfaces such as stained glass, ceramics, metals, wood or ironed concrete.

Substrate Condition:

The substrate must be dry, firm, well adhered, even and free of any impurities that could hinder the perfect bonding of the product.

Substrate Preparation:

If the substrate has traces of dust, grease, dirt and/or other impurities, undertake exhaustive cleaning to guarantee adequate adherence.

If the substrate is not well adhered, remove the non-adherent areas by scraping and brushing.

If the substrate has salt deposits, brush and apply *Neutralysal Premium*.

Application method:

Shake well until homogenous then apply one coat evenly. Does not require dilution, apply product as is.

Drying:

At 25 ° C (77°C) and 60% relative humidity: 24 hours.

Ambient conditions:

The working temperature (ambient and substrate) must be between +5 °C and +40 °C (41 °F and 104 °F). Do not apply under direct sunlight or on surfaces heated by the sun.

Tools:

Roller or brush.

Tool cleaning:

Clean tools after use with warm water.

Notes

Mineral substrates must be at least 28 days old.

Do not apply to surfaces in permanent contact with water.

In case of rain, let the surface dry at least 24 hours before application.

It is recommended to protect the treated surface from rain before application.

Parts that are not going to be treated should be protected (glassware or carpentry).

To maintain product efficacy do not mix with other brands.

ADDITIONAL INFORMATION

Usage warnings:

None, particularly in situations where normal product application is expected and by people without any specific medical conditions. Alkaline product, protect skin and eyes especially. Do not inhale the product. Keep out of reach of children.

Waste management:

According to local legal regulations. The containers are made of polypropylene. Please contribute to the protection of the environment, do not throw waste down the drain and use the nearest recycling point.

Sustainability gesture:

Minimise product waste by carefully estimating the amount you will need. Store any unused product for future use according to the "Storage" guidelines.

Safety information:

For information regarding safety, physical, ecological and toxicological details please see the latest version of the product's Material Safety Data Sheet.

Technical Support:

For further information, please contact your local distributor or manufacturer.

(technicalsupport@graphenstone.com).

The information provided is given in good faith, based on current knowledge and IEdiSA's experience with the products when they are properly stored, handled and applied in normal situations and in accordance with the recommendations of IEdiSA. The Technical Specifications sheet is useful for information and consulting but is not legally binding. In particular, it does not exempt the user from testing and verifying the suitability of the product for the desired application and purpose. Any modification to the instructions and recommendations by the user, he will assume all the corresponding risk and responsibility. IEdiSA reserves the right to modifications that improve the product or its application. This version invalidates previous ones.