



# Lacq Hardwoodoil

Lacq Hardwoodoil is a traditional recipe of blended vegetable oils to protect and maintain wooden garden furniture, ramps or teak decks annually. This Hardwoodoil has a very high solids content (98%), which means that a very high coverage is achieved with the first layer. Provides long-term protection from dirt or ageing for, among others, teakwood and bankirai. This Hardwoodoil is very easy to apply.

## Applicable to:

- Garden furniture
- Decking
- Outdoor wood

## Processing:

1. The surface must be dry, free of dust and grease. Also remove any algae and moss first fouling and possible weathered (grayed) spots in the wood. Use for graying of the hardwood a good degreasing agent. We advise to use the Lacq Turbogel for this use.
2. Apply with a flat brush, roller or lint-free cloth. Leave for twenty minutes withdraw and remove the excess oil with a lint-free cloth. On highly absorbent surfaces can be applied a second layer wet-on-wet.
3. Attention: build-up of layer thickness on the substrate must be prevented.
4. When you see "chapped" spots in the wood after complete drying, because this is not complete is saturated, repeat the treatment.
5. Do not process below 5 °C and above a relative humidity of 85 °C.

*Pay attention! Always put on a sample first to see if you get the desired finish. This can differ per wood type. Hardwoodoil is only for impregnation, so it is not possible layer thickness.*

## Coverage:

About 6-9 m<sup>2</sup> per liter.

*Pay attention! Efficiency always depends on the structure, suction of the wood, the thickness of the layer, the tools used and the conditions of application.*

## Drying time:

Dust dry:	approx. 6 hours.
Recoatable after:	approx. 16 hours.
Min. processingtemperature:	5 °C.
Max. processingtemperature:	25 °C.

## Cleaning:

Clean tools with turpentine.

*Pay attention! There is a risk of scalding and fire with the textiles used. Always pour with water and allow to dry thoroughly.*

## Technical features:

Moisture regulating effect:	Yes.
Protection in years:	5 years.
Substance:	Liquid.

## Available quantities:

1L, 2,5L, 5L & 20L.

## Shelf life:

2 years in original unopened packaging, frost-free, in a dry place (temperature between 5 °C and 35 °C). Avoid freezing during transport and storage.

## Safety information:

For detailed safety information, please consult the MSDS. MSDS is available on [www.lacq.eu](http://www.lacq.eu).

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.