

Lacq Specials Pure Tungoil

Lacq Specials pure Tungoil protects almost all wood surfaces naturally against weather influences, water, alcohol and food acids. Pure Tungoil is a natural oil and already found centuries have been applied to wooden surfaces for indoors and outdoors. Pure Tungoil provides a long-lasting matte finish.

Applicable on wooden kitchen utensils:

- Chopping boards
- Salad bowls
- Worktop

Processing:

- 1. Lacq Specials Tungoil is ready for use. Apply the oil with a brush or a lint-free one cotton cloth. Let the oil soak in for 20 to 30 minutes (depending on the wood).
- 2. Then wipe off the excess oil with a lint-free cotton cloth. Pay attention! Wipe the excess oil before it becomes sticky.
- 3. Then let the oil dry for 24 hours.
- 4. Repeat these steps for multiple layers. For porous surfaces or surfaces that too we recommend 4 layers.
- 5. When the desired number of coats has been applied, allow the oil to fully drain for a few days to dry.

Pay attention! Always put on a sample first to see if you get the desired finish. This can differ per wood type. Tungoil gives the wooden surface a warm glow when you touch it wet the surface gives it an indication of the end result.

Maintenance:

Clean the covered surface with a damp cloth. When spills are encountered located on the surface, wipe away immediately. For stubborn stains, you can use a mild cleaner such as Fluxaf Power-Clean. The surface will, depending on the use and wood type be oiled once or twice a year. For outdoor use it is important to have enough layers are established for protection.

Coverage:

About 12 m² per liter.

Pay attention! Efficiency always depends on the structure, suction of the wood, the thickness of the layer, the tools used and the conditions of application.

Drying time:

Dust dry: approx. 1 hour. Recoatable after: approx. 48 hours.

Min. processing temperature: $5 \, ^{\circ}$ C. Max. processing temperature: $25 \, ^{\circ}$ C.

Cleaning:

Clean tools with turpentine.

Pay attention! Used cloths can ignite due to scalding. Pour the used textiles over with water and let dry extensively outdoors or store in an airtight container.

Technical feautures:

Moisture regulating effect: Yes.
Protection in years: 5 years.
Substance: Liquid.

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.

Available quantities:

0,25L.

Available colors:

Colorless.

Shelf life:

2 years in original unopened packaging, frost-free, in a dry place (temperature between 5 °C and 35 °C). Avoid freezing during transport and storage.

Safety information:

For detailed safety information, please consult the MSDS. MSDS is available on www.lacq.eu.

Pay attention! Tungoil comes from a nut tree and may be suitable for people with a nut allergy response concerns.