

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 24/05/2023 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: 405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)
UFI	: V9YP-X2NA-300A-1ET9
Product code	: 10430
Type of product	: Paint
Product group	: Blend
Other means of identification	: 405/F158/ ALL COLOURS

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

No additional information available

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Teal & Mackrill Ltd
Lockwood Street
Hull – East Yorkshire HU2 0HN
England
T +44 (0)1482 320194
info@teamac.co.uk

Distributor

Teal & Mackrill EU B.V.
Queens Towers
Delflandlaan 1
1062 EA Amsterdam
Netherlands
T +31 (0)208 004828
info@teamac.co.uk

1.4. Emergency telephone number

Emergency number : +44 (0) 1482 320194 Teamac (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Warning

Contains

: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics; HYDROCARBONS, C9, AROMATICS

405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	: H226 - Flammable liquid and vapour. H336 - May cause drowsiness or dizziness. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC-No.: 919-857-5 REACH-no: 01-2119463258-33	$\geq 30 - < 50$	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
Calcium Carbonate substance with a Community workplace exposure limit	CAS-No.: 1317-65-3 EC-No.: 215-279-6	$\geq 10 - < 30$	Not classified
TRIZINC BIS(ORTHOPHOSPHATE)	CAS-No.: 7779-90-0 EC-No.: 231-944-3 EC Index-No.: 030-011-00-6 REACH-no: 01-2119485044-40	$\geq 5 - < 10$	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Titanium Dioxide substance with national workplace exposure limit(s) (GB)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 REACH-no: 01-2119489379-17	$\geq 5 - < 10$	Not classified
Diatomaceous Earth substance with national workplace exposure limit(s) (GB)	CAS-No.: 61790-53-2 EC-No.: 310-127-6	$\geq 1 - < 5$	Not classified

405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
C.I. Pigment Yellow substance with national workplace exposure limit(s) (GB)	CAS-No.: 6358-31-2 EC-No.: 228-768-4	≥ 1 – < 5	Not classified
HYDROCARBONS, C9, AROMATICS substance with national workplace exposure limit(s) (GB)	CAS-No.: 64742-95-6 EC-No.: 918-668-5 REACH-no: 01-2119455851-35	≥ 1 – < 5	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Zinc Oxide	CAS-No.: 1314-13-2 EC-No.: 215-222-5 EC Index-No.: 030-013-00-7 REACH-no: 01-2119463881-32	< 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics substance with national workplace exposure limit(s) (GB)	EC-No.: 918-481-9 REACH-no: 01-2119457273-39	< 1	Asp. Tox. 1, H304
Dipropylene Glycol Methyl Ether substance with national workplace exposure limit(s) (GB)	CAS-No.: 34590-94-8 EC-No.: 252-104-2 REACH-no: 01-2119450011-60	< 1	Not classified
ETHANOL substance with national workplace exposure limit(s) (GB)	CAS-No.: 64-17-5 EC-No.: 200-578-6 REACH-no: 01-2119457610-43	< 1	Flam. Liq. 2, H225 Eye Irrit. 2, H319
2,6-Di-tert-butyl-p-cresol substance with national workplace exposure limit(s) (GB)	CAS-No.: 128-37-0 EC-No.: 204-881-4 REACH-no: 01-2119565113-46	< 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
METHANOL substance with national workplace exposure limit(s) (GB)	CAS-No.: 67-56-1 EC-No.: 200-659-6	< 1	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Inhalation), H331 (ATE=0.5 mg/l/4h) STOT SE 1, H370

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Never give anything by mouth to an unconscious person.
First-aid measures after inhalation	: Move the affected person away from the contaminated area and into the fresh air. Administer oxygen if breathing is difficult. If unconscious place in recovery position and seek medical advice.
First-aid measures after skin contact	: Take off contaminated clothing. Wash contaminated clothing before reuse. Gently wash with plenty of soap and water.

405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do not induce vomiting. If swallowed, seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Get medical attention if symptoms occur after washing.
-------------------------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: dry chemical powder, alcohol-resistant foam, carbon dioxide (CO ₂).
------------------------------	---

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour. Vapours may cause fire/explosion if source of ignition is present.
-------------	---

5.3. Advice for firefighters

Precautionary measures fire	: Cool down the containers exposed to heat with a water spray.
Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid inhalation of the product. Avoid contact with skin and eyes. No open flames. No smoking. Eliminate every possible source of ignition.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment	: Cover spill with non combustible material, e.g.: sand, earth, vermiculite. Collect spillage.
Methods for cleaning up	: Notify authorities if product enters sewers or public waters. Clean contaminated surfaces with an excess of water.

6.4. Reference to other sections

See Section 8. For further information refer to section 13.

405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.
- Precautions for safe handling : Do not eat, drink or smoke when using this product. Provide local exhaust or general room ventilation. Do not breathe vapours.
- Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.
- Storage conditions : Store in original container. Store in a well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Incompatible products : Oxidizing agent. Strong bases. Strong acids.
- Storage temperature : 5 – 25 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

METHANOL (67-56-1)

United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	266 mg/m ³
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	333 mg/m ³
WEL STEL (OEL STEL) [ppm]	250 ppm

ETHANOL (64-17-5)

United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	1920 mg/m ³
WEL TWA (OEL TWA) [2]	1000 ppm

Calcium Carbonate (1317-65-3)

EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	10 mg/m ³ Inhalable Dust
----------	-------------------------------------

405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

C.I. Pigment Yellow (6358-31-2)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	1.5 mg/m ³ Total Dust
Titanium Dioxide (13463-67-7)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	10 mg/m ³ Inhalable dust
Diatomaceous Earth (61790-53-2)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	1.2 mg/m ³ respirable dust
Dipropylene Glycol Methyl Ether (34590-94-8)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	308 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
HYDROCARBONS, C9, AROMATICS (64742-95-6)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	19 mg/m ³ (8 hour)
WEL TWA (OEL TWA) [2]	100 ppm (8 hour)
2,6-Di-tert-butyl-p-cresol (128-37-0)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	10 mg/m ³
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	1000 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation. Do not exceed the occupational exposure limits (OEL).

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves.

405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Hand protection:

Nitrile rubber gloves. As a general principal, exposure should be managed by means other than the provision of protective gloves. Permeation time: minimum >480min long term exposure; material / thickness [mm]: Breakthrough time : refer to the recommendations of the supplier

Other skin protection

Materials for protective clothing:

Use protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

In case of inadequate ventilation wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Various colours.
Appearance	: Viscous liquid.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: ~ 38°C Closed cup.
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Technically not feasible.
Viscosity, kinematic	: > 20.5 mm ² /s
Viscosity, dynamic	: 3.5 @ 25°C
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1.37 – 1.41 @ 20°C
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Avoid ignition sources.

10.5. Incompatible materials

Strong acids. Strong bases. Oxidizing agent.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
	pH: Technically not feasible.

HYDROCARBONS, C9, AROMATICS (64742-95-6)

pH	Not available.
Serious eye damage/irritation	: Not classified
	pH: Technically not feasible.

HYDROCARBONS, C9, AROMATICS (64742-95-6)

pH	Not available.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

METHANOL (67-56-1)

STOT-single exposure	Causes damage to organs.
----------------------	--------------------------

405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
STOT-single exposure	May cause drowsiness or dizziness.
HYDROCARBONS, C9, AROMATICS (64742-95-6)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)	
Viscosity, kinematic	> 20.5 mm ² /s
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Viscosity, kinematic	≤ 20.5 mm ² /s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.
Not rapidly degradable

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not discharge into drains or rivers. Disposal must be done according to official regulations.
Additional information : Dispose of waste cans and containers according to local regulations.

405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

European List of Waste (LoW) code	: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances 15 01 02 - plastic packaging 15 01 04 - metallic packaging
HP Code	: HP3 - "Flammable:" – flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; – flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; – flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; – flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; – water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; – other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name				
PAINT	PAINT	Paint	PAINT	PAINT
Transport document description				
UN 1263 PAINT, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1263 Paint, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	3	3
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				


405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 650
Limited quantities (ADR)	: 5L
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T2
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	: 
Tunnel restriction code (ADR)	: D/E
EAC code	: •3Y

Transport by sea

Special provisions (IMDG)	: 163, 223, 367, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T2
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Miscibility with water depends upon the composition.

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3, A72, A192
ERG code (IATA)	: 3L

Inland waterway transport

Classification code (ADN)	: F1
Special provisions (ADN)	: 163, 367, 650
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01
Number of blue cones/lights (ADN)	: 0

405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Rail transport

Classification code (RID)	: F1
Special provisions (RID)	: 163, 367, 650
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T2
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBF
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE4
Hazard identification number (RID)	: 30

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Abbreviations and acronyms:

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
DNEL	Derived-No Effect Level
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
SDS	Safety Data Sheet
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
VOC	Volatile Organic Compounds
PBT	Persistent Bioaccumulative Toxic
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
STOT SE 1	Specific target organ toxicity – single exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

405/F158 - METALCOTE PRIMER / UNDERCOAT (All colours except white)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.