

TECHNICAL DATASHEET

Issue date:
July 2020

SELEMIX[®] TEXTURE POWDER ADDITIVES 6-560 FINE / 6-561 COARSE

PRODUCT DESCRIPTION

Selemix 6-560 and 6-561 are polyethylene powder paint additives in fine and coarse granular texture respectively.

They create a uniform finely texture surface and provide a good abrasion resistance.

The texture powder additives are compatible with all Selemix System 1K and 2K topcoats without any impact on color and on drying process. They are also compatible with 8-552/3 and 8-110/1 Selemix Waterborne Topcoats.

The choice of the type of the grain size (fine or coarse) and the percentage of use from 3 to 5% on finished enamel depends on the desired level of textured of the surface.

PRODUCTS



6-560	<i>Selemix</i> Texture Powder Additive Fine
6-651	<i>Selemix</i> Texture Powder Additive Coarse

SUBSTRATES AND PREPARATION

Refer to the relevant Selemix Topcoat Technical Datasheet


MIXING

6-560 and 6-561 are supplied in a 200g plastic bottle. The bottle has a measuring cap able to contain 15 g of powder additive. Thoroughly mix paint before activating and check colour before use
 Add hardener and thinner according to the Selemix Topcoat TDS

	Features Standard System	Conventional Air-Assisted Airless
	By Weight: Selemix Topcoat 6-560 / 6-561 Texture Additive	1000 30-50
	By Volume: Selemix Topcoat 6-560 / 6-561 Texture Additive	1 Litre 2-3 capfuls

APPLICATION

Refer to the relevant Selemix Topcoat Technical Datasheet

	Features	Conventional	Air-Assisted Airless
	Spraygun setup:	We recommend using the biggest nozzle diameter suggested in topcoat technical data sheet	It is always recommended to contact the pump supplier as the powder particles may cause a fast wear and tear of the mechanical parts and of the membranes.

TECHNICAL DATA

Data for Additives as supplied:	
Particle Size:	
Fine Texture 6-560:	Average 24-36 Microns (Maximum 90 microns)
Coarse Texture 6-561:	Average 60-90 Microns (Maximum 125 microns)
Specific Gravity:	0.949
Solids Content:	100%
Solvent Content:	0%
VOC (g/L)	0g/L

PRODUCT CODES AND DESCRIPTIONS

Selemix Code	Short Code	Product Description	Packsize	
1.965.6000/E0.2K	6-560	Selemix Texture Powder Additive Fine	0.2	K
1.965.6100/E0.2K	6-561	Selemix Texture Powder Additive Coarse	0.2	K

HEALTH AND SAFETY

For comprehensive Health, Safety and Environmental advice, please refer to the relevant Material Safety Data Sheets and Product can labels.

THIS PRODUCT IS FOR PROFESSIONAL USE ONLY

The information given in this sheet is for guidance only. Any person using the product without first making further enquiries as to the stability of the product for the intended purpose does so at his own risk and we can accept no liability for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of our experience and our policy of continuous product development. Drying times quoted are average times at 20°C. Film thickness, humidity and shop temperature can all affect drying times.

FOR FURTHER INFORMATION PLEASE CONTACT:

Selemix Customer Service and Sales Group
Needham Road
Stowmarket, Suffolk
IP14 2AD, England
Tel: 01449 771771