

# Technical Data Sheet

Rust-Oleum uPVC Paint (Brush)

---

**Recolour and protect weathered and worn uPVC and composite doors, window frames, conservatories, fascias, drain pipes, guttering and much more with Rust-Oleum uPVC Paint. With a durable smooth matt finish, it brings a new lease of life and colour to your dated and discoloured uPVC.**

**The paint is self-priming and dries in just 1 hour.**

- **Water-based with virtually no odour.**
- **No primer needed.**
- **10 year performance.\***
- **Weather resistant finish.**
- **Mould and algae resistant.**
- **Exceptional coverage.**
- **Highly concentrated.**
- **Colour-fast - will not fade.**

**Preparation:** Ensure surface is clean, dry and free from contamination. Ensure any mould or mildew has been removed and if necessary, treat surfaces with a proprietary fungicidal solution. If painting over hard, glossy existing paint abrade the surface before application. To ensure paint suitability test on a small inconspicuous area first.

**Application:** Stir thoroughly before use. The product may be applied by brush, roller or electric paint sprayer. If rolling, use a short to medium nap mohair roller. If spraying, paint should be diluted with water by 10-20% as required. Two coats are recommended. Temperature at time of application and during drying should be between 10° - 25°C.

**Coverage:** Up to 14m<sup>2</sup>/L per coat.

**Drying Time:** Touch dry in 1 hour. Hard dry in 4 hours. May be over coated after 4 hours.

**Clean Up:** Remove as much product as possible from application equipment before washing with water. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste paint.

**Limitations:** Temperature at time of application and during drying should be greater than 10°C. Do not apply in direct sunlight or if rain is imminent. Not suitable for roof areas or areas where ponding water occurs, or surfaces that will be immersed in water. Not suitable for painting over vinyl wrapped doors.

**Shelf Life:** 2 years (unopened) from date of manufacture. (See base of can).

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements. A copy of the appropriate health and safety should be consulted prior to use.