

Technical Data Sheet

Rust-Oleum Painter's Touch (Brush Paint) 250ml (15 colours) & 20ml (25 colours)

Ideal for use on wood, metal, most plastics, paper and most other surfaces. Please test on a small area first to check adhesion and compatibility.

Interior & Exterior Use

Directions: Stir well before use. Use only when temperature is between 10-32°C and humidity is below 85% to ensure proper drying. Previously painted surfaces should be lightly abraded to provide a key. Bare metal and wood should be suitably primed prior to painting. Apply paint with a soft brush using light even strokes taking care to avoid unsightly runs.

Drying: Dries to touch in 30-60minutes.

Drying times are based on warm (15°C), dry application conditions with good ventilation. Lower temperatures and higher humidity will prolong the drying times.

Recoating: Allow at least 2 hours between coats. 2 coats recommended.

Cleaning: Clean brushes immediately after use with water.

Coverage: 250ml – 1.25m² (inc. 2 coats) depending on surface profile/porosity.

A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product.

Shelf Life: 2 years (unopened) from date of manufacture. (See base of can).

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements.

Toy Standard Testing: BS EN71:3:2013 incorporating corrigendum July 2013 , EN71-3 2013 *^ Soluble Chromium (V1) content. EU Limit value for this product (Cat A/i):140g/l. This Product contains a maximum of 40g/l VOC.

Tor Coatings Limited, Portobello Industrial Estate, Birtley, Chester-le-Street, Co. Durham, DH3 2RE, UK.

Technical Services Department: 0191 410 6611

E-mail: info@tor-coatings.com www.tor-coatings.com or www.rustoleumspraypaint.com

03/02/2016