



SAFETY DATA SHEET
201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name 201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL
Product No. 201/C264/2/R

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses As an anti-climb paint

1.3. Details of the supplier of the safety data sheet

Supplier COO-VAR
Lockwood Street
Hull
HU2 0HN
+44 (0) 1482 328053(T)
+44 (0) 1482 219266(F)
info@coo-var.co.uk
Contact Person Technical Department - 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri as above

1.4. Emergency telephone number

+44 (0) 1482 328053 (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (1999/45/EEC) F+;R12. R52/53, R66, R67.

Human health

Gas or vapour is harmful on prolonged exposure or in high concentration. In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling contents of this container is dangerous and can be fatal.

Environment

The product contains a substance which is very toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

Physical and Chemical Hazards

The product is extremely flammable and may ignite in the air at normal temperature and pressure. Explosive vapour/air mixtures may be spontaneously formed. Aerosol containers can explode when heated, due to excessive pressure build-up. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Do not pierce or burn even after use.

2.2. Label elements

Labelling



Extremely flammable

Risk Phrases

R12 Extremely flammable.

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL

Safety Phrases	R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R66	Repeated exposure may cause skin dryness or cracking.
	R67	Vapours may cause drowsiness and dizziness.
	A1	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
	A2	Do not spray on a naked flame or any incandescent material.
	S2	Keep out of the reach of children.
	S9	Keep container in a well-ventilated place.
	S16	Keep away from sources of ignition - No smoking.
	S23	Do not breathe vapour/spray.
	S37	Wear suitable gloves.
	S51	Use only in well-ventilated areas.
	S56	Dispose of this material and its container to hazardous or special waste collection point.

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

WHITE SPIRIT	10-30%
CAS-No.:	EC No.: 919-446-0 Registration Number: 01-2119458049-33-XXXX
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xn;R65. N;R51/53. R10,R66,R67.
PROPANE	10-30%
CAS-No.: 74-98-6	EC No.: 200-827-9
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12
BUTANE	10-30%
CAS-No.: 106-97-8	EC No.: 203-448-7
Classification (EC 1272/2008) Flam. Gas 1 - H220	Classification (67/548/EEC) F+;R12
Carbon Black	1-5%
CAS-No.: 1333-86-4	EC No.: 215-609-9 Registration Number: 01-2119384822-32
Classification (EC 1272/2008) Not classified.	Classification (67/548/EEC) Not classified.

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL

Low Aromatic White Spirit		1-5%
CAS-No.:	EC No.: 919-857-5	Registration Number: 01-2119463258-33-XXXX
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H336 Asp. Tox. 1 - H304	Classification (67/548/EEC) Xn;R65. R10,R66,R67.	
ETHANOL		<1%
CAS-No.: 64-17-5	EC No.: 200-578-6	Registration Number: 01-2119457610-43-xxxx
Classification (EC 1272/2008) Flam. Liq. 2 - H225	Classification (67/548/EEC) F;R11	
XYLENE, MIXED ISOMERS		<0.1%
CAS-No.: 1330-20-7	EC No.: 215-535-7	Registration Number: 01-2119488216-32-xxxx
Classification (EC 1272/2008) Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304	Classification (67/548/EEC) Xn;R20/21,R65. Xi;R36/37/38. R10.	
METHANOL		<0.1%
CAS-No.: 67-56-1	EC No.: 200-659-6	
Classification (EC 1272/2008) Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370	Classification (67/548/EEC) F;R11 T;R23/24/25,R39/23/24/25	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious.

Inhalation

In case of inhalation of spray mist: Move person into fresh air and keep at rest. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion

Immediately rinse mouth and provide fresh air. DO NOT induce vomiting. Get medical attention immediately.

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL

Skin contact

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above.

DO NOT use solvents or thinners

Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information

If adverse symptoms develop as described the casualty should be transferred to hospital as soon as possible.

Inhalation

No specific symptoms noted.

Ingestion

No specific symptoms noted.

Skin contact

No specific symptoms noted.

Eye contact

May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No specific first aid measures noted.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

Unusual Fire & Explosion Hazards

Extremely flammable. Forms explosive mixtures with air. May travel considerable distance to source of ignition and flash back. Aerosol cans may explode in a fire.

Specific hazards

Aerosol containers can explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Special Fire Fighting Procedures

Water spray should be used to cool containers. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Avoid inhalation of vapours and aerosol spray.

6.2. Environmental precautions

Do not allow to enter drains, sewers or watercourses. Contain spillages with sand, earth or any suitable adsorbent material.

6.3. Methods and material for containment and cleaning up

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb spillage with non-combustible, absorbent material. Let evaporate. Keep out of confined spaces because of explosion risk.

6.4. Reference to other sections

The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See section 12 as well.

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray near naked flame or any incandescent material.

7.2. Conditions for safe storage, including any incompatibilities

Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Do not pierce or burn even after use.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
BUTANE	WEL	600 ppm	1450 mg/m ³	750 ppm	1810 mg/m ³	Carc
Carbon Black	WEL		3,5 mg/m ³		7 mg/m ³	
ETHANOL	WEL	1000 ppm	1920 mg/m ³			
Low Aromatic White Spirit	WEL		1000 mg/m ³			
METHANOL	WEL	200 ppm(Sk)	266 mg/m ³ (Sk)	250 ppm(Sk)	333 mg/m ³ (Sk)	
PROPANE		Asphyxiating	Asphyxiating	Asphyxiating	Asphyxiating	
WHITE SPIRIT	WEL		350 mg/m ³			
XYLENE, MIXED ISOMERS	WEL	50 ppm	220 mg/m ³	100 ppm	441 mg/m ³	Sk

WEL = Workplace Exposure Limit.

Carc = Capable of causing cancer and/or heritable genetic damage.

Sk = Can be absorbed through skin.

Ingredient Comments

SUP = Supplier's recommendation.

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL**Low Aromatic White Spirit**

DNEL				
Consumer	Oral	Long Term	Systemic Effects	300 mg/kg/day
Consumer	Dermal	Long Term	Systemic Effects	300 mg/kg/day
Industry	Dermal	Long Term	Systemic Effects	300 mg/kg/day
Industry	Inhalation.	Long Term	Systemic Effects	1500 mg/m3
Consumer	Inhalation.	Long Term	Systemic Effects	900 mg/m3

No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

WHITE SPIRIT

DNEL				
Consumer	Oral	Long Term	Systemic Effects	1040 mg/kg/day
Consumer	Dermal	Long Term	Systemic Effects	1040 mg/kg/day
Consumer	Inhalation.	Long Term	Systemic Effects	710 mg/m3
Consumer	Inhalation.	Short Term	Systemic Effects	570 mg/m3
Industry	Inhalation.	Short Term	Systemic Effects	570 mg/m3
Industry	Inhalation.	Long Term	Systemic Effects	1980 mg/m3
Industry	Dermal	Long Term	Systemic Effects	1056 mg/kg/day

XYLENE, MIXED ISOMERS (CAS: 1330-20-7)

DNEL				
Consumer	Oral	Long Term	Systemic Effects	12.5 mg/kg/day
Consumer	Dermal	Long Term	Systemic Effects	1872 mg/kg/day
Consumer	Inhalation.	Long Term	Systemic Effects	65.3 mg/m3
Consumer	Inhalation.	Short Term	260	mg/m3
Industry	Dermal	Long Term	Systemic Effects	3182 mg/kg/day
Industry	Inhalation.	Long Term	Systemic Effects	221 mg/m3
Industry	Inhalation.	Short Term	442	mg/m3

No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of spray.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used.

Hand protection

Due to the packaging form, aerosol, risk of skin contact is small. For prolonged or repeated skin contact use suitable protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

Eye protection

Use eye protection. Wear approved chemical safety goggles where eye exposure is reasonably probable.

Other Protection

Wear appropriate clothing to prevent reasonably probable skin contact.

Hygiene measures

Wash hands after handling. Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin.

Personal protection

When using do not smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Appearance	Aerosol.
Colour	Black.
Odour	of solvents

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL

Flash point (°C)	<-40 °C
Auto Ignition Temperature (°C)	410 - 580
Flammability Limit - Lower(%)	1.8%
Flammability Limit - Upper(%)	9.5%
Comments	Information given concerns the major ingredient. 23 Flammable gas

9.2. Other information

Volatile Organic Compound (VOC) <400 g/litre

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Not applicable.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials To Avoid

Strong acids. Strong oxidising substances.

10.6. Hazardous decomposition products

In case of fire, toxic gases (CO, CO₂, NO_x) may be formed.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

General information

Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

Inhalation

Irritating to respiratory system.

Ingestion

May cause discomfort if swallowed.

Skin contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Eye contact

Irritating and may cause redness and pain.

Health Warnings

Arrhythmia, (deviation from normal heart beat). In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Route of entry

Inhalation. Ingestion. Skin and/or eye contact.

Target Organs

Eyes Skin Respiratory system, lungs

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL

Medical Symptoms

Arrhythmia, (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness.

Toxicological information on ingredients.

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL**Low Aromatic White Spirit****Acute toxicity:**

Acute Toxicity (Oral LD50)

> 5000 mg/kg Rat

Acute Toxicity (Dermal LD50)

> 5000 mg/kg Rabbit

Acute Toxicity (Inhalation LC50)

> 5 mg/l (vapours) Rat 4 hours

Skin Corrosion/Irritation:

Erythema/scar score

Very slight erythema -barely perceptible (1). Well defined erythema (2).

Oedema score

No oedema (0).

Slightly irritating.

Serious eye damage/irritation:

Not Irritating.

Respiratory or skin sensitisation:

Not sensitising.

Skin sensitisation

Guinea pig maximization test (GPMT): Guinea Pig

Not Sensitising.

Germ cell mutagenicity:

Genotoxicity - In Vitro

Chromosome aberration:

Negative.

This substance has no evidence of mutagenic properties.

Carcinogenicity:

Inhalation. Rat

This substance has no evidence of carcinogenic properties. Does not contain any substances known to be carcinogenic.

Reproductive Toxicity:

Reproductive Toxicity - Fertility

Fertility: Inhalation. Rat

This substance has no evidence of toxicity to reproduction.

Reproductive Toxicity - Development

Developmental toxicity: Inhalation. Rat

This substance has no evidence of toxicity to reproduction.

Specific target organ toxicity - repeated exposure:

STOT - Repeated exposure

Not available.

Aspiration hazard:

Viscosity

Kinematic viscosity <= 20.5 mm²/s.

Inhalation

Vapours may cause drowsiness and dizziness. Central nervous system depression.

Ingestion

Harmful: danger of serious damage to health by prolonged exposure if swallowed.

Skin contact

Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL

Eye contact

No specific health warnings noted.

Route of entry

Inhalation. Ingestion.

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL
WHITE SPIRIT

Other Health Effects

This substance has no evidence of carcinogenic properties.

Acute toxicity:

Acute Toxicity (Oral LD50)

> 15000 mg/kg Rat

Minimally toxic via ingestion

Acute Toxicity (Dermal LD50)

~ 3400 mg/kg Rabbit

Not corrosive to skin Not irritating

Acute Toxicity (Inhalation LC50)

> 13.1 mg/l (vapours) Rat 4 hours

Serious eye damage/irritation:

Not Irritating.

Respiratory or skin sensitisation:

Respiratory sensitisation

Not determined.

There is evidence that the material can lead to respiratory hypersensitivity.

Not Sensitising.

Carcinogenicity:

Carcinogenicity

NOAEL 300 mg/kg Oral Rat

Reproductive Toxicity:

Reproductive Toxicity - Fertility

One-generation study: NOAEL >3000 mg/kg/day Oral Rat P

Reproductive Toxicity - Development

Developmental toxicity: NOAEC >300 ppm Inhalation. Rat

Specific target organ toxicity - single exposure:

Target Organs

Central nervous system

Specific target organ toxicity - repeated exposure:

STOT - Repeated exposure

NOAEL 1056 mg/kg Oral Rat

Aspiration hazard:

Viscosity

Kinematic viscosity <= 20.5 mm²/s.

Inhalation

No specific health warnings noted.

Ingestion

Harmful: may cause lung damage if swallowed. May cause stomach pain or vomiting.

Skin contact

May cause defatting of the skin, but is not an irritant. Not a skin sensitiser.

Eye contact

No specific health warnings noted.

Route of entry

Skin and/or eye contact. Inhalation.

Central nervous system

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL**SECTION 12: ECOLOGICAL INFORMATION****Ecotoxicity**

The product has not been tested but contains ingredients which are toxic or very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses.

12.1. Toxicity**Acute Fish Toxicity**

Likely to be harmful to aquatic organisms.

Ecological information on ingredients.**Low Aromatic White Spirit****Acute Toxicity - Fish**

LC50 96 hours > 1000 mg/l Onchorhynchus mykiss (Rainbow trout)

Substance did not cause acute toxicity to fish

EC 50, 48 Hrs, Daphnia, mg/l

>1000

Substance did not cause acute toxicity to the freshwater invertebrates

Acute Toxicity - Aquatic Plants

EC50 72 hours > 1000 mg/l Freshwater algae

Substance did not cause acute toxicity to the freshwater green algae

EC50 > 100 mg/l Activated sludge

Chronic Toxicity - Fish Early life Stage

NOEC 28 days 0.131 mg/l Onchorhynchus mykiss (Rainbow trout)

Chronic Toxicity - Aquatic Invertebrates

NOEC 28 days 0.23 mg/l Daphnia magna

WHITE SPIRIT

Dangerous for the environment if discharged into watercourses Toxic to aquatic organisms

LC 50, 96 Hrs, Fish mg/l

10 - 30

EC 50, 48 Hrs, Daphnia, mg/l

10 - 22

IC 50, 72 Hrs, Algae, mg/l

4.6 - 10

Chronic Toxicity - Aquatic Invertebrates

NOEC 21 days < 0.28 mg/l Daphnia magna

12.2. Persistence and degradability**Degradability**

There are no data on the degradability of this product.

Ecological information on ingredients.**Low Aromatic White Spirit****Degradability**

The product is easily biodegradable.

Oxidises rapidly by photo-chemical reactions in air

Biodegradation

Degradation (80%) 28 days

Test - 301F Ready Biodegradability - Manometric Respiratory Test

WHITE SPIRIT**Degradability**

The product is easily biodegradable.

Biodegradation

Degradation (75%) 28 days

12.3. Bioaccumulative potential

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL

Bioaccumulative potential

No data available on bioaccumulation.

Ecological information on ingredients.**Low Aromatic White Spirit**

Bioaccumulative potential

The product contains potentially bioaccumulating substances.

Partition coefficient

5 - 6.7

WHITE SPIRIT

Bioaccumulation factor

Scientifically unjustified.

Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.

12.4. Mobility in soil

Mobility:

Not determined

Ecological information on ingredients.**Low Aromatic White Spirit**

Mobility:

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Readily absorbed into soil.

Adsorption/Desorption Coefficient

Not available.

Surface tension

24.5 mN/m 20 °C

WHITE SPIRIT

Adsorption/Desorption Coefficient

Scientifically unjustified.

Volatilisation is dependent on Henry's Law constant (HLC) which is not applicable to complex substances.

12.5. Results of PBT and vPvB assessment

Not Classified as PBT/vPvB by current EU criteria.

Ecological information on ingredients.**Low Aromatic White Spirit**

Not Classified as PBT/vPvB by current EU criteria.

WHITE SPIRIT

Not Classified as PBT/vPvB by current EU criteria.

12.6. Other adverse effects

Not determined.

Ecological information on ingredients.**Low Aromatic White Spirit**

Not known.

WHITE SPIRIT

This substance may contribute to ozone formation in the near surface atmosphere. However, the photochemical formation of ozone depends on a complex interaction of other atmospheric pollutant sources and environmental conditions. Therefore, the contribution of this substance to ozone formation is outside the scope of this substance assessment and is more appropriately addressed via EU air quality directives.

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Do not puncture or incinerate even when empty.

13.1. Waste treatment methods

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). DO NOT BURN OR INCINERATE CONTAINERS EVEN WHEN EMPTY - CONTAINERS MAY BURST OR EXPLODE VIOLENTLY IF EXPOSED TO EXTREME HEAT.

SECTION 14: TRANSPORT INFORMATION

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following.

14.1. UN number

UN No. (ADR/RID/ADN)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

14.2. UN proper shipping name

Proper Shipping Name	AEROSOL DISPENSERS, NOS
----------------------	-------------------------

14.3. Transport hazard class(es)

ADR/RID/ADN Class	3
ADR/RID/ADN Class	Class 3: Flammable liquids.
ADR Label No.	3
IMDG Class	3
ICAO Class/Division	3
Transport Labels	

**14.4. Packing group**

ADR/RID/ADN Packing group	III
IMDG Packing group	III
ICAO Packing group	III

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant
No.

14.6. Special precautions for user

EMS	F-D, S-U
Hazard No. (ADR)	23 Flammable gas.
Tunnel Restriction Code	(E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL**SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Uk Regulatory References

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health. The Aerosol Dispensers Regulations 1977 & 1999.

Approved Code Of Practice

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138] British Aerosol Manufacturers Code of Practice 7th. Edition 1999.

Guidance Notes

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

National Regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. The Aerosol Dispensers (EEC Requirements) (Amendment) Regulations 1996 (S.I 1996 No. 2421).

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Comments

Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 453/2010 Revision to sections 2, 8, 11 & 12 for reclassification of solvents.

Issued By	Technical Dept. (P.E.)
Revision Date	26/04/2012
Revision	3
Supersedes date	26/04/2012
SDS No.	11064
Safety Data Sheet Status	Approved.
Date	Date printed _____
Signature	Initials _____

Risk Phrases In Full

R12	Extremely flammable.
R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R11	Highly flammable
R36/37/38	Irritating to eyes, respiratory system and skin.
NC	Not classified.
R66	Repeated exposure may cause skin dryness or cracking.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R67	Vapours may cause drowsiness and dizziness.

201/C264 - VANDALENE (ANTI-CLIMB PAINT) AEROSOL

Hazard Statements In Full

H370	Causes damage to organs <<Organs>>.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H220	Extremely flammable gas.
H224	Extremely flammable liquid and vapour.
H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H312	Harmful in contact with skin.
H412	Harmful to aquatic life with long lasting effects.
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs <<Organs>> through prolonged or repeated exposure if inhaled.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.
EUH066	Repeated exposure may cause skin dryness or cracking.
H331	Toxic if inhaled.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.