

TH0 Cleaning Solvent

TH0

intended uses

For cleaning of solvent based and solvent free materials from application equipment.

product description

A blend of dimethyl adipate, dimethyl glutarate and dimethyl succinate.

product information

Product reference	TH0
Volume solids	N/A
Typical thickness	N/A
Theoretical coverage	N/A
Practical coverage	N/A
Appearance/Colour range	N/A
VOC content	1000 g/litre

application details

Mix ratio	N/A
Method of application	N/A
Thinner	N/A
Cleaner	N/A
Pot Life	N/A
Drying time	N/A

Substrate Temperature	Touch Dry	Hard Dry	Overcoating Interval	
			Minimum	Maximum
20°C	-	N/A	-	

storage and handling

Storage Store the closed containers in a store room which is either in a safe place or is a fire resisting structure. The storage and conditions must meet the statutory requirements of The Highly Flammable Liquids and Petroleum Gases Regulations 1972.

Pack Size	5 litres
Flash point	102°C
Product weight	1 kilo/litre
Shelf life	5 years in unopened containers

surface preparation

N/A

limitations

Must be stored in accordance with The Highly Flammable Liquids and Petroleum Gases Regulations 1972.

NB. A high flash version (flash point above 32°C) is available Ref Tor TH27.

safety precautions

A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product. This can be faxed if urgently required.

Minimum precautions for all paints:

1. Avoid skin and eye contact i.e. wear gloves, goggles, etc
2. Ensure good ventilation, mechanical if necessary.
3. Store and use away from heat and flame.
4. Do not eat or smoke in the vicinity of work.
5. Wash hands before eating.
6. Refer to supply container for additional warning labels.

definitions

Tolerances

All information quoted in this data sheet is subject to normal manufacturing tolerances.

Practical coverage

Practical coverage can vary considerably depending on method of application, surface roughness, weather conditions and complexity of the structure.

Pot Life

Applies only to two component products and refers to the time the mixture remains usable.

disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Tor Coatings be liable for consequential or incidental damages.

This document will normally be updated at least every two years. It is the users responsibility to ensure that they have the current copy.

Updated: April 2016
TH0

STOCKIST INFORMATION

Rawlins Paints | Northspeed House | Holbeck | Leeds | LS11 9NF
T: 0113 2455450 / E: sales@rawlinspaints.com
W: www.rawlinspaints.com