

PRODUCT NAME

Hardener 9004 Standard

ORIGINALLY ISSUED

21/02/2006

VERSION

1.0

PRODUCT CODE

CUR9004

VERSION DATE

21/02/2006



PRODUCT DESCRIPTION

A medium solids Isocyanate Hardener for use in recommended HMG 2K systems.

Mixing Instructions appear on the Base Component.



IMPORTANT INSTRUCTIONS BEFORE USE

- Read and follow SDS, TDS and label instructions
- Stir all paints thoroughly before use
- Always use the same batch number on the same job
- Check colour & sheen. HMG will not accept any discrepancies arising after use
- Filter the product immediately before use
- Reduce emissions and maintain quality by replacing tin lid after use
- If in any doubt speak HMG Technical Service Department on (0161) 205 7631



VOC CONTENT

0.580Kg/L



GENERAL INFORMATION

Flashpoint

27°C

Storage

Store between 5°C - 25°C. When not in use, cans must be kept sealed

Shelf Life

12 months from delivery date in original sealed containers



HEALTH AND SAFETY

- Refer to SDS and tin label prior to use.
- Refer to JD11/77 health and safety data sheet.
- RFU product contains isocyanates. Suitable air fed respiratory equipment should be worn when spraying.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of HMG's knowledge and belief accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use. For professional use only.