

SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/8

205 Flexible Joint Filler - Curing Agent

Revision 1
 Revision date 2020-03-02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	205 Flexible Joint Filler - Curing Agent
--------------	--

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC9a] Coatings and paints, thinners, paint removers;
-------------	---

1.3. Details of the supplier of the safety data sheet

Company	EJ Rawlins & Co. Ltd
Address	Northspeed House Moorview Holbeck Leeds LS11 9NF
Web	www.rawlinspaints.com
Telephone	0113 2455450
Fax	0113 2452649
Email	info@rawlinspaints.com
Email address of the competent person	info@rawlinspaints.com

1.4. Emergency telephone number


Emergency telephone number	0113 2455450 08:30-17:00
----------------------------	-----------------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412;
--------------------------------------	---

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Acute Tox. 4: H302 - Harmful if swallowed. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Skin Sens. 1: H317 - May cause an allergic skin reaction. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Precautionary Statement: Prevention	P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling.

205 Flexible Joint Filler - Curing Agent

Revision 1
Revision date 2020-03-02

2.2. Label elements

Precautionary Statement: Response	P270 - Do not eat, drink or smoke when using this product. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor/ /if you feel unwell. P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P302+P352 - IF ON SKIN: Wash with plenty of water/ . P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 -Immediately call a POISON CENTER/doctor/ . P321 - Specific treatment (see on this label). P330 - Rinse mouth. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P363 - Wash contaminated clothing before reuse.
Precautionary Statement: Storage	P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
3-Aminomethyl-3,5,5-trimethylcyclohexylamine	612-067-00-9	2855-13-2	220-666-8	01-2119514687-32		Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412;
Benzyl alcohol	603-057-00-5	100-51-6	202-859-9	01-2119492630-38		Acute Tox. 4: H332; Acute Tox. 4: H302;
m-xylolenediamine		1477-55-0	216-032-5	01-2119480150-50		Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Acute Tox. 4: H332; Aquatic Chronic 3: H412;
trimethylhexamethylenediamine		25620-58-0	247-134-8	01-2119560598-25		Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove Contact Lenses.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
Eye contact	Risk of serious damage to eyes.
Skin contact	May cause irritation to skin.
Ingestion	Causes burns. Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

205 Flexible Joint Filler - Curing Agent

Revision 1
Revision date 2020-03-02**4.3. Indication of any immediate medical attention and special treatment needed**

Inhalation	If you feel unwell, seek medical advice (show the label where possible).
Eye contact	Seek medical attention.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam, Water. Do NOT use water jet.
--	--

5.2. Special hazards arising from the substance or mixture

	Corrosive. Burning produces irritating, toxic and obnoxious fumes.
--	--

5.3. Advice for firefighters

	Wear self contained breathing apparatus and protective clothing.
--	--

Further information

	Dispose of as special waste in compliance with official regulations.
--	--

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Wear suitable protective equipment. Avoid contact with skin and eyes.
--	---

6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

6.4. Reference to other sections

	See section 8 for further information. See section 13 for further information.
--	--

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in original container.
--	---


7.3. Specific end use(s)

	See section 1.2 for further information.
--	--

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

	This product does not contain any relevant quantities of materials with critical values that have to be monitored in the workplace.
--	---

8.2. Exposure controls

	
--	---

205 Flexible Joint Filler - Curing Agent

Revision 1

Revision date 2020-03-02

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear suitable protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves. Butyl rubber gloves.
Skin protection - Other	Wear suitable protective clothing.
Respiratory protection	Wear suitable respiratory equipment when necessary.
Occupational exposure controls	Keep away from food, drink and animal feedingstuffs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Amber
Odour	Characteristic
pH	No data available
Melting point	No data available
Freezing Point	No data available
Initial boiling point	> 100 °C
Flash point	132 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Vapour pressure	No data available
Vapour density	No data available
Relative density	No data available
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Viscosity	350 mPas (Cone & Plate)
Explosive properties	No data available
Oxidising properties	No data available
Odour threshold	No data available
Solubility	Slightly soluble in water

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	0 %
Lead content	0 %
VOC (Volatile organic compounds)	0 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

	Stable under normal conditions.
--	---------------------------------

10.2. Chemical stability

	Stable under normal conditions.
--	---------------------------------

205 Flexible Joint Filler - Curing Agent

Revision 1

Revision date 2020-03-02

10.3. Possibility of hazardous reactions

	Reacts with Acids, Alkalis, Oxidising Agents.
--	---

10.4. Conditions to avoid

	Heat.
--	-------

10.5. Incompatible materials

	Strong oxidising agents.
--	--------------------------

10.6. Hazardous decomposition products

	No data is available on this product.
--	---------------------------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation	Causes burns.
Serious eye damage/irritation	Risk of serious damage to eyes.
Respiratory or skin sensitisation	May cause sensitisation by skin contact.
Germ cell mutagenicity	No mutagenic effects reported.
Reproductive toxicity	No observed effect level. No teratogenic effects reported.

11.1.4. Toxicological Information

3-Aminomethyl-3,5,5-trimethylcy clohexylamine	Dermal Rat LD50: >2000mg/kg	Oral Rat LD50: 1030mg/kg
	Dermal Rabbit LD50: 1840mg/kg	
Benzyl alcohol	Oral Rat LD50: 1230mg/kg	Dermal Rabbit LD50: 2000mg/kg
trimethylhexamethylenediamine	Oral Rat LD50: 910mg/kg	

11.1.13. Other information

	Swallowing will lead to a strong caustic effect on mouth and throat and danger of perforation of esophagus and stomach.
--	---

SECTION 12: Ecological information

12.1. Toxicity

3-Aminomethyl-3,5,5-trimethylcy clohexylamine	Daphnia EC50/48h: 23 mg/l	Algae IC50/72h: 50.0000 mg/l
	Fish LC50/96h: 110.0000 mg/l	
Benzyl alcohol	Daphnia EC50/48h: 400.0000 mg/l	Algae IC50/72h: 640.0000 mg/l
	Fish LC50/96h: 645.0000 mg/l	
trimethylhexamethylenediamine	Daphnia EC50/48h: 31.5 mg/l	Algae IC50/72h: 29.5000 mg/l
	Fish LC50/96h: 1000.0000 mg/l	

12.2. Persistence and degradability

	No data is available on this product.
--	---------------------------------------

PBT

	Not applicable.
--	-----------------

12.3. Bioaccumulative potential

	No data is available on this product.
--	---------------------------------------

Partition coefficient

	205 Flexible Joint Filler - Curing Agent No data available
--	--

205 Flexible Joint Filler - Curing Agent

Revision 1

Revision date 2020-03-02

12.4. Mobility in soil

Slightly miscible in water.

12.5. Results of PBT and vPvB assessment

No data is available on this product.

12.6. Other adverse effects

No data is available on this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of in compliance with all local and national regulations.

General information

08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS.

08 02 wastes from MFSU of other coatings (including ceramic materials).

08 02 99 wastes not otherwise specified.

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Disposal of packaging

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Do NOT reuse empty containers.

SECTION 14: Transport information

Hazard pictograms



14.1. UN number

UN2735

14.2. UN proper shipping name

AMINES, LIQUID, CORROSIVE N.O.S. (Contains Isophorone Diamine)

14.3. Transport hazard class(es)

ADR/RID	8
Subsidiary risk	-
IMDG	8
Subsidiary risk	-
IATA	8

205 Flexible Joint Filler - Curing Agent

Revision 1

Revision date 2020-03-02

14.3. Transport hazard class(es)

Subsidiary risk	-
-----------------	---

14.4. Packing group

Packing group	III
---------------	-----

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

14.6. Special precautions for user

	Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of a spillage.
--	---

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

	For transport approval see regulatory information.
--	--

ADR/RID

Hazard ID	80
Tunnel Category	(E)

IMDG

EmS Code	F-A S-B
----------	---------

IATA

Packing Instruction (Cargo)	856
Maximum quantity	60 L
Packing Instruction (Passenger)	852
Maximum quantity	5 L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

	<p>REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p> <p>COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p>
--	--

15.2. Chemical safety assessment

	This product contains substances for which Chemical Safety Assessments are still required.
--	--

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas:. 4 - Eye contact.
Text of Hazard Statements in Section 3	Acute Tox. 4: H302 - Harmful if swallowed. Acute Tox. 4: H312 - Harmful in contact with skin. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

205 Flexible Joint Filler - Curing Agent

Revision 1

Revision date 2020-03-02

Other information

	Skin Sens. 1: H317 - May cause an allergic skin reaction. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Acute Tox. 4: H332 - Harmful if inhaled. Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled
Maximum content of VOC	0 g/l.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--