

Technical Data Sheet

Rust-Oleum Garden Furniture Paint (Brush)
(Available in a range of 8 colours)

Renovate and transform garden furniture with Rust-Oleum Chalky Finish Garden Furniture Paint. With an ultra durable, scrubbable, soft touch matt finish, it brings a new lease of life and colour to garden furniture. The paint can be directly applied to wood (bare or painted), brick, stone, plaster or any suitably primed rigid surface (metal, plastic etc).

Preparation: Ensure surface is clean, dry and free from contamination. If wax or oil has previously been used on the item, clean the surface thoroughly with white spirit. If painting over hard, glossy existing paint abrade the surface before application.

Application: Stir thoroughly before use. The product may be applied by brush or roller. If applying by brush, apply evenly, following the grain of the wood. If rolling, use a short to medium nap mohair roller. Two coats are recommended.

Coverage: Up to 14m²/L per coat. Coverage may vary depending upon application method, rate of application and porosity of the surface.

Drying Time: Touch dry in 1 hour. Hard dry in 4 hours. May be over coated after 4 hours.

Clean Up: Remove as much product as possible from application equipment before washing with water. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste paint.

Limitations: Not for use directly onto metal. Use a suitable metal primer if necessary. Not a stain blocking product. Prime any surfaces where stain bleed may be an issue, including knots. Temperature at time of application and during drying should be greater than 10°C. Do not apply if rain is imminent.

Shelf Life: 2 years (unopened) from date of manufacture. (See base of can).

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements. A copy of the appropriate health and safety should be consulted prior to use.