

# Technical Data Sheet

Rust-Oleum Gloss Furniture Paint

---

**Make a statement with a bold, gloss paint finish on furniture. Specially designed to give a durable and long-lasting gloss effect on wood (*bare or painted*), brick, stone, plaster or any suitable primer rigid surface. No priming necessary on most surfaces.**

- **Modern high sheen gloss finish.**
- **Highly concentrated.**
- **No priming or sanding necessary\*.**
- **Works great over old paint and varnish.**
- **Apply directly onto wood, brick, stone, plaster or any suitably primer rigid surface (*eg. metal, plastic, etc*).**
- **No need to wax or lacquer the finished paint work.**
- **Certified Toy Safe to EN 71-3:2013+A3:2019.**

**Preparation:** For best results, ensure surface is clean and free from wax or oil. If wax has been used clean the surface thoroughly with white spirit. We recommend that bare wood should be sanded before painting.

**Application:** Stir thoroughly prior to use. The product may be applied by brush or roller. If applying by brush, apply evenly following the grain of the wood. If rolling, use a short nap mohair roller. Two coats recommended.

**Coverage:** Up to 14m<sup>2</sup> / litre. Coverage may vary depending upon method and rate of application and porosity of surface.

**Drying Time:** Touch dry in 1 hour. Handle after 4 hours. Apply a second coat after 4 hours, if necessary.

**Clean Up:** Remove as much product as possible from application equipment before washing with water. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

**Limitations:** Not for use directly onto metal. Not a stain-blocking product. Prime any surfaces where stain bleed may be an issue, including knots, with a suitable stain primer. Advisable to use a primer/sealer on very porous surfaces. If unsure, test on an inconspicuous area before painting. Not recommended for outdoor use. Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process colour/finish shown is for guidance only. To ensure paint suitability test on a small inconspicuous area first.

**Shelf Life:** 2 years (unopened) from date of manufacture. (See base of can).

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements. A copy of the appropriate health and safety should be consulted prior to use.

This product contains a maximum of 35g/l VOC.

\*No priming or sanding necessary on most surfaces, refer to the limitations section if unsure.