

# Technical Data Sheet

Rust-Oleum Matt Furniture Paint

---

Renovate and transform furniture with Rust-Oleum Washable Matt Furniture Paint. The soft touch, matt finish is both extremely durable and washable and can be directly applied to wood (*bare or painted*), brick, stone, plaster, most plastics, paper, or any suitably primed rigid surface (*metal, plastic, etc*). No priming or sanding required on most surfaces.

- Water based with virtually no odour.
- Extremely durable, smooth matt finish.
- Highly concentrated.
- Exceptional coverage.
- No priming or sanding necessary on most surfaces (*simply ensure surfaces are smooth, dry & free from contaminants*).
- Can be applied over old paint & varnish.
- No need to wax or lacquer the finished paint work.
- Suitable for interior furniture restoration projects.
- Certified Toy Safe to EN 71-3:2013+A3:2019.

**Preparation:** Ensure surface is smooth, clean, dry and free from wax, polish, oil or any other surface contaminants liable to cause adhesion problems. Previously painted / varnished surfaces should be lightly abraded to provide a key. Bare metal should be suitably primed prior to painting. Prime any surfaces where stain blocking will be an issue such as knots or tannin bleed from timber with an appropriate stain blocking primer.

**Application:** Stir thoroughly before use. Use only when the temperature is between 10-32°C and humidity is below 85% to ensure proper drying. Apply by brush or short nap mohair roller. If applying by brush, apply evenly following the grain of the wood.

**Coverage:** Up to 14m<sup>2</sup> / litre per coat. Two coats normally applied.

**Drying Time:** Touch dry after 1 hour. Hard dry in 4 hours. Recoat after 2 hours.

**Clean Up:** Remove as much product as possible from application equipment before washing with water. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

**Limitations:** Coverage may vary depending upon method and rate of application and porosity of surface. Drying times are based on warm (20°C), dry application conditions with good ventilation. Lower temperatures and higher humidity will prolong the drying times. Not recommended for outdoor use. Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process colour/finish shown is for guidance only. To ensure paint suitability test on a small inconspicuous area first.

**Shelf Life:** 2 years (unopened) from date of manufacture. (See base of can).

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements. A copy of the appropriate health and safety should be consulted prior to use.

This product contains a maximum of 1g/l VOC.