

Technical Data Sheet

Rust-Oleum Satin Finish Furniture Paint

An elegant, satin paint finish for the renovation of old furniture. The paint can be used directly onto wood (bare or painted), brick, stone, plaster or any suitably primed rigid surface. No priming or sanding necessary on most surfaces.

Preparation: For best results, ensure surface is clean and free from wax or oil. If wax has been used clean the surface thoroughly with white spirit. We recommend that bare wood should be sanded before painting.

Application: Stir thoroughly prior to use. The product may be applied by brush or roller. If applying by brush, apply evenly following the grain of the wood. If rolling, use a short nap mohair roller. Two coats recommended.

Coverage: Up to 14m² / litre. Coverage may vary depending upon method and rate of application and porosity of surface.

Drying Time: Touch dry in 1 hour. Handle after 4 hours. Apply a second coat after 4 hours, if necessary. Full hardness after 4 hours.

Clean Up: Remove as much product as possible from application equipment before washing with water. Do not empty into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

Limitations: Not for use directly onto metal. Not a stain-blocking product. Prime any surfaces where stain bleed may be an issue, including knots with a suitable stain blocking primer. Advisable to use a primer/sealer on very porous surfaces. If unsure, test on an inconspicuous area before painting. Not recommended for outdoor use.

Tor Coatings Limited, Portobello Industrial Estate, Birtley, Chester-le-Street, Co. Durham, DH3 2RE, UK.

Technical Services Department: 0191 410 6611

E-mail: info@tor-coatings.com or www.tor-coatings.com or www.rustoleumspraypaint.com

Shelf Life: 2 years (unopened) from date of manufacture. (See base of can).

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements. A copy of the appropriate health and safety should be consulted prior to use.